
DATA SHEET

MODEL EC 11/2 X 11/4 NICKEL ALUMINUM BRONZE






TE	EFC MOTO	R	DIMENSIONS IN INCHES (For Reference Only)								APPROX.	
HP	RPM	FRAME	A (typ)	B (typ)	D	Е	F	Н	L	СР	OP	WEIGHT (LBS)
3	1750	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	14-5/8	24-15/16	11	156
3	3500	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	14-5/8	24-15/16	11	156
5	3500	184TCZ	8-5/8	6-1/2	4-1/2	3-3/4	5-1/2	13/32	14-5/8	24-15/16	11	169
7-1/2	3500	213TCZ	9-1/2	8	5-1/4	4-1/4	5-1/2	13/32	15-1/4	26-9/16	11-3/4	237

PART NAME	NICKEL ALUMINUM BRONZE				
Casing, Cover & Impeller	AMPCO® 483				
Wear Ring	AMPCO® 18				
Motor Shaft	Steel				
Shaft Sleeve	AMPCO® 18				
Adapter	Cast Iron				







MODEL EC 11/2 X 11/4 NICKEL ALUMINUM BRONZE

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EC 11/2 X 11/4 STAINLESS STEEL





TE	EFC MOTO	R	DIMENSIONS IN INCHES (For Reference Only)								APPROX. WEIGHT	
HP	RPM	FRAME	A (typ)	B (typ)	D	E	F	Н	L	CP	OP	(LBS)
3	1750	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	14-5/8	24-15/16	11	156
3	3500	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	14-5/8	24-15/16	11	156
5	3500	184TCZ	8-5/8	6-1/2	4-1/2	3-3/4	5-1/2	13/32	14-5/8	24-15/16	11	169
7-1/2	3500	213TCZ	9-1/2	8	5-1/4	4-1/4	5-1/2	13/32	15-1/4	26-9/16	11-3/4	237

PART NAME	STAINLESS STEEL				
Casing, Cover & Impeller	316 Stainless				
Wear Ring	316 Stainless				
Motor Shaft	Steel				
Shaft Sleeve	316 Stainless				
Adapter	Cast Iron				





MODEL EC 11/2 X 11/4 STAINLESS STEEL

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EC 2 X 11/2





TE	FC MOTO	R	DIMENSIONS IN INCHES (For Reference Only)							APPROX. WEIGHT		
HP	RPM	FRAME	A (typ)	B (typ)	D	E	F	Н	L	СР	OP	(LBS)
3	1750	182TCZ	8-5/8	8-5/8	4-1/2	3-3/4	4-1/2	13/32	14-9/16	24-7/8	11-1/4	164
3	3500	182TCZ	8-5/8	8-5/8	4-1/2	3-3/4	4-1/2	13/32	14-9/16	24-7/8	11-1/4	159
5	3500	184TCZ	8-5/8	8-5/8	4-1/2	3-3/4	5-1/2	13/32	14-9/16	24-7/8	11-1/4	172
7-1/2	3500	213TCZ	9-1/2	9-1/2	5-1/4	4-1/4	5-1/2	13/32	15-3/16	26-1/2	12	240
10	3500	215TCZ	9-1/2	9-1/2	5-1/4	4-1/4	7	13/32	15-3/16	26-1/2	12	262

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL		
Casing, Cover & Impeller	AMPCO® 483	316 Stainless		
Wear Ring	AMPCO® 18	316 Stainless		
Motor Shaft	Steel	Steel		
Shaft Sleeve	AMPCO® 18	316 Stainless		
Adapter	Cast Iron	Cast Iron		




MODEL EC 2 X 11/2


Curves show approximate characteristics based on clear 68° water.

Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EC 21/2 X 2





TE	FC MOTO	R	DIMENSIONS IN INCHES (For Reference Only)								APPROX. WEIGHT	
HP	RPM	FRAME	A (typ)	B (typ)	D	E	F	Н	L	СР	OP	(LBS)
3	1750	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	14-9/16	24-5/8	11-11/16	166
5	3500	184TCZ	8-5/8	6-1/2	4-1/2	3-3/4	5-1/2	13/32	14-9/16	24-5/8	11-11/16	179
7-1/2	3500	213TCZ	9-1/2	8	5-1/4	4-1/4	5-1/2	13/32	15-3/16	26-1/2	12-7/16	246
10	3500	215TCZ	9-1/2	8	5-1/4	4-1/4	7	13/32	15-3/16	26-1/2	12-7/16	265
15	3500	215TCZ	9-1/8	8	5-1/4	4-1/4	7	13/32	15-3/16	27-5/8	12-7/16	362

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL		
Casing, Cover & Impeller	AMPCO® 483	316 Stainless		
Wear Ring	AMPCO® 18	316 Stainless		
Motor Shaft	Steel	Steel		
Shaft Sleeve	AMPCO® 18	316 Stainless		
Adapter	Cast Iron	Cast Iron		




MODEL EC 21/2 X 2


Curves show approximate characteristics based on clear 68° water.

Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EC/ECH 3 x 2 1/2





TE	FC МОТО	R		DIMENSIONS IN INCHES (For Reference Only)								APPROX.
HP	RPM	FRAME	A (typ)	B (typ)	D	E	F	Н	L	CP	OP	WEIGHT (LBS)
3	1750	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	15-7/16	25-3/4	11-1/4	216
5	3500	184TCZ	8-5/8	6-1/2	4-1/2	3-3/4	5-1/2	13/32	15-7/16	25-3/4	11-1/4	224
7-1/2	3500	213JP	9-1/2	8	5-1/4	4-1/4	5-1/2	13/32	17-1/8	28-3/16	12	258
10	3500	215JP	9-1/2	8	5-1/4	4-1/4	7	13/32	17-1/8	28-3/16	12	276
15	3500	254JP	11-1/2	9-3/4	6-1/4	5	8-1/4	17/32	17-3/8	30-15/16	13	378
20	3500	256JP	11-1/2	11-1/2	6-1/4	5	10	17/32	17-3/8	32-1/4	13	416
25	3500	284JP	12-3/4	12-3/4	7	5-1/2	9-1/2	17/32	17-3/8	35-13/16	13-3/4	516

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL		
Casing, Cover & Impeller	AMPCO® 483	316 Stainless		
Wear Ring	AMPCO® 18	316 Stainless		
Motor Shaft	Steel	Steel		
Shaft Sleeve	AMPCO® 18	316 Stainless		
Adapter	Cast Iron	Cast Iron		





MODEL EC/ECH 3 x 2 1/2

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EC/ECH 4x3





TE	FC МОТО	R		DIMENSIONS IN INCHES (For Reference Only)							APPROX. WEIGHT	
HP	RPM	FRAME	A (typ)	B (typ)	D	E	F	Н	L	CP	0P	(LBS)
10	3500	215JP	9-1/2	8	5-1/4	4-1/4	7	13/32	17-9/16	28-5/8	11-3/4	295
15	3500	254JP	11-1/2	9-3/4	6-1/4	5	8-1/4	17/32	17-13/16	30-1/4	12-3/4	403
20	3500	256JP	11-1/2	11-1/2	6-1/4	5	10	17/32	17-13/16	32-11/16	12-3/4	441
25	3500	284JP	12-3/4	12-3/4	7	5-1/2	9-1/2	17/32	17-13/16	36-1/4	13-1/2	572
30	3500	286JP	12-3/4	12-3/4	7	5-1/2	11	17/32	17-13/16	36-1/4	13-1/2	701
3	1750	182TCZ	8-5/8	6-1/2	4-1/2	3-3/4	4-1/2	13/32	16-1/4	26-9/16	11	209
5	1750	184TCZ	8-5/8	6-1/2	4-1/2	3-3/4	5-1/2	13/32	16-1/4	26-9/16	11	237

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL			
Casing, Cover & Impeller	AMPCO® 483	316 Stainless			
Wear Ring	AMPCO® 18	316 Stainless			
Motor Shaft	Steel	Steel			
Shaft Sleeve	AMPCO® 18	316 Stainless			
Adapter	Cast Iron	Cast Iron			





MODEL EC/ECH 4x3

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EP 11/2 X 11/4 NICKEL ALUMINUM BRONZE





TE	FC MOTO	R	DI	MENSIONS	S IN INCHES (For Reference Only)			
HP	RPM	FRAME	HA	HD	HE	HF	HG	НО
1	1750	143T	12	8-1/2	4-3/4	33-3/8	3	15
2	3500	145T	12	8-1/2	4-3/4	33-3/8	3	15
3	3500	182T	15	8-7/8	5-3/4	19	3-3/8	15-3/8
5	3500	184T	15	8-7/8	5-3/4	19	3-3/8	15-3/8
7-1/2	3500	213T	15	8-7/8	5-3/4	19	3-3/8	15-3/8

PART NAME	NICKEL ALUMINUM BRONZE		
Casing, Cover & Impeller	AMPCO® 483		
Wear Ring	AMPCO® 18		
Shaft	Steel		
Shaft Sleeve	AMPCO® 18		
Frame	Cast Iron		





MODEL EP 11/2 X 11/4 NICKEL ALUMINUM BRONZE

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.







### Ampco Pumps Company

DATA SHEET


MODEL EP 11/2 X 11/4 STAINLESS STEEL





TE	FC MOTO	R	DI	MENSIONS	S IN INCHES (For Reference Only)			
HP	RPM	FRAME	HA	HD	HE	HF	HG	НО
1	1750	143T	12	8-1/2	4-3/4	33-3/8	3	15
2	3500	145T	12	8-1/2	4-3/4	33-3/8	3	15
3	3500	182T	15	8-7/8	5-3/4	19	3-3/8	15-3/8
5	3500	184T	15	8-7/8	5-3/4	19	3-3/8	15-3/8
7-1/2	3500	213T	15	8-7/8	5-3/4	19	3-3/8	15-3/8

PART NAME	STAINLESS STEEL		
Casing, Cover & Impeller	316 Stainless		
Wear Ring	316 Stainless		
Shaft	Steel		
Shaft Sleeve	316 Stainless		
Frame	Cast Iron		





MODEL EP 11/2 X 11/4
STAINLESS STEEL

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.







### Ampco Pumps Company

DATA SHEET


MODEL EP 2 X 11/2





TE	FC MOTO	R	DI	MENSIONS	S IN INCHES (For Reference Only)			
HP	RPM	FRAME	HA	HD	HE	HF	HG	НО
1	1750	143T	12	8-1/2	4-3/4	33-3/8	3	15-1/4
2	3500	145T	12	8-1/2	4-3/4	33-3/8	3	15-1/4
3	3500	182T	15	8-7/8	5-3/4	19	3-3/8	15-5/8
5	3500	184T	15	8-7/8	5-3/4	19	3-3/8	15-5/8
7-1/2	3500	213T	15	8-7/8	5-3/4	19	3-3/8	15-5/8

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL
Casing, Cover & Impeller	AMPCO® 483	316 Stainless
Wear Ring	AMPCO® 18	316 Stainless
Shaft	Steel	Steel
Shaft Sleeve	AMPCO® 18	316 Stainless
Frame	Cast Iron	Cast Iron





MODEL EP 2 X 11/2

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EP 21/2 X 2





TE	FC MOTO	R	DI	MENSIONS IN INCHES (For Reference Only)				
HP	RPM	FRAME	НА	HD	HE	HF	HG	НО
2	1750	145T	12	8-1/2	4-3/4	33-3/8	3	15-7/16
5	3500	184T	15	8-7/8	5-3/4	19	3-3/8	15-13/16
7-1/2	3500	213T	15	8-7/8	5-3/4	19	3-3/8	15-13/16
10	3500	215T	15	8-7/8	5-3/4	19	3-3/8	15-13/16
15	3500	254T	15	9-5/8	6	23	3-3/8	16-13/16

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL
Casing, Cover & Impeller	AMPCO® 483	316 Stainless
Wear Ring	AMPCO® 18	316 Stainless
Shaft	Steel	Steel
Shaft Sleeve	AMPCO® 18	316 Stainless
Frame	Cast Iron	Cast Iron





MODEL EP 21/2 X 2

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.






### Ampco Pumps Company

DATA SHEET


MODEL EP/EPH 3 X 2 1/2





TEFC MOTOR			DIMENSIONS IN INCHES (For Reference Only)					
HP	RPM	FRAME	Α	В	C	L		
7-1/2	3500	213T	3-7/8	9-3/8	19	36-3/4		
10	3500	215T	3-7/8	9-3/8	19	36-3/4		
15	3500	254T	4-1/8	9-5/8	23	41-1/2		
20	3500	256T	4-1/8	9-5/8	23	41-1/2		
25	3500	284T	4-7/8	10-3/8	23	45-1/2		

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL
Casing, Cover & Impeller	AMPCO® 483	316 Stainless
Wear Ring	AMPCO® 18	316 Stainless
Shaft	Steel	Steel
Shaft Sleeve	AMPCO® 18	316 Stainless
Frame	Cast Iron	Cast Iron





MODEL EP/EPH 3 x 21/2

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.







### Ampco Pumps Company

DATA SHEET


MODEL EP/EPH 4x3





TEFC MOTOR			DIMENSIONS IN INCHES (For Reference Only)					
HP	RPM	FRAME	НВ	HD	HE	HF	НО	
10	3500	215T	36-3/4	8-7/8	6	19	15-3/8	
15	3500	254T	41-1/2	9-5/8	6	23	16-1/8	
20	3500	256T	41-1/2	9-5/8	6	23	16-1/8	
25	3500	284TS	41-1/2	10-3/8	5-3/4	23	16-7/8	
30	3500	286TS	41-1/2	10-3/8	5-3/4	23	16-7/8	

PART NAME	NICKEL ALUMINUM BRONZE	STAINLESS STEEL
Casing, Cover & Impeller	AMPCO® 483	316 Stainless
Wear Ring	AMPCO® 18	316 Stainless
Shaft	Steel	Steel
Shaft Sleeve	AMPCO® 18	316 Stainless
Frame	Cast Iron	Cast Iron





MODEL EP/EPH 4x3

Curves show approximate characteristics based on clear 68° water.
Rated point is guaranteed.

E Series pumps provide the same heavy-duty construction and hydraulic performance as Ampco's Z Series.

An enlarged stuffing box offers multiple sealing arrangements, including Type 21, Type 1, Type 9, Double Type 21, Double Type 9, packing and cartridge seals.





### Ampco Pumps Company