

## **G** Slimline

STAINLESS STEEL SUBMERSIBLE PUMP FOR 4" AND LARGER WELLS

5, 7 & 10 GPM - UP TO 11/2 HP - VFD COMPATIBLE





# Effortless installations come standard with the slim design of the G Series

#### **FEATURES**


- Slim design for ease of installation: The pump's slim diameter of 3.75" allows for easier installation in tight wells.
- Powered for continuous operation: All ratings are within the working limits of the motor as recommended by the motor manufacturer.
  Pump can be operated continuously without damage to the motor.
- Field Serviceable: Units are field serviceable with common tools and readily available repair parts.
- Sand Handling Design: The face clearance and floating stack has proven itself for over 40 years as a durable and superior design. Includes wrap-around suction strainer.
- Corrosion Resistance: New stainless steel discharge head and motor adapter combined with stainless steel casing and cable guard.
- Check Valve: An integrated spring-loaded check valve makes it easily replaceable without disassembly.







#### **MODEL 7G**

### **MODEL 10G**







#### **PRODUCT SPECIFICATIONS**

Model	Flow Range GPM	Horsepower Range	Best Efficiency GPM	Discharge Connection	Minimum Well Size	Rotation <sup>®</sup>	Effective Diameter
5G	1.2 - 7.5	1/2-11/2	5	1.25"	4"	CCW	3.75″
7G	1.5 - 10		7				
10G	2 - 12		10				

① Rotation is counterclockwise when observed from pump discharge end.

Series	Model	Doguirod UD	Stages	Water End		
Series	Model	Required HP		Length (in)	Wt. (lbs)	
	5G05	.5	15	15.1	9	
5 <b>G</b>	5G07	.75	20	18.2	11	
30	5G10	1	25	22.5	14	
	5G15	1.5	34	28.2	17	
	7G05	.5	11	12.5	7	
7 <b>G</b>	7G07	.75	15	15.1	9	
76	7G10	1	20	18.2	11	
	7G15	1.5	25	22.5	14	
	10G05	.5	12	14.7	8	
10G	10G07	.75	15	16.8	9	
100	10G10	1	20	20.3	10	
	10G15	1.5	27	26.3	16	



Xylem Inc.

Phone: (866) 325-4210 • Fax: (888) 322-5877 www.xylem.com/gouldswatertechnology