

# Gas Engine-Driven, Cast Iron

## Models 1536 and 1539



### Upgrade Options:

- Increase dry-run and abrasive resistance with Life Guard Seals
  - Life Guard seals are the OEM standard

### Features

- Briggs & Stratton® engine (EPA & CARB certified)
- Close-coupled, gas engine-driven
- Max. fluid temperature: 140°F/60°C
- Housing: cast iron
- Impeller: Nylon
- Pump seals: Viton/ceramic standard; Life Guard silicon carbide available
- Life Guard seals are the industry standard on OEM equipment
- Weight: 53 lbs./24.1 kg

### Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Port Size	Engine Mfg. & HP
1536	110	416	75	5.2	1-1/2" x 1-1/4"	Briggs & Stratton® 5.5 hp
1539	Same as model 1536 without mounting base					
1538*	1-1/2" x 1-1/4" centrifugal pump kit. DOES NOT include engine.					
3430-0332	Seal and o-ring repair kit					
3430-0589	Life Guard silicon carbide seal kit					

\* Must use threaded shaft engine.

### 1536, 1539

### U.S. Units

GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI
110	106	96	87	73	50

### 1536, 1539

### Metric Units

LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR
416	401	363	329	276	189

Briggs & Stratton® is a registered trademark of Briggs & Stratton Corporation.

# Gas Engine-Driven, Cast Iron

## Models 1537 and 1540



### Upgrade Options:

- Increase dry-run and abrasive resistance with Life Guard Seals
  - Life Guard seals are the OEM standard

### Features

- Honda® engine (EPA & CARB certified)
- Close-coupled, gas engine-driven
- Max. fluid temperature: 140°F/60°C
- Housing: cast iron
- Impeller: Nylon
- Pump seals: Viton/ceramic standard; Life Guard silicon carbide available
- Life Guard seals are the industry standard on OEM equipment
- Weight: 53 lbs./24.1 kg

### Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Port Size	Engine Mfg. & HP
1537	110	416	80	5.5	1-1/2" x 1-1/4"	Honda® 5.5 hp
1540	Same as model 1537 without mounting base					
1538*	1-1/2" x 1-1/4" centrifugal pump kit. DOES NOT include engine.					
3430-0332	Seal and o-ring repair kit					
3420-0589	Life Guard silicon carbide seal kit					

\* Must use threaded shaft engine.

### 1537, 1540

### U.S. Units

GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI	GPM at 70 PSI
110	106	96	88	80	60	30

### 1537, 1540

### Metric Units

LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR	LPM at 4.8 BAR
416	401	363	333	303	227	114

Viton® is a registered trademark of DuPont.