

# Gas Engine-Driven Transfer Pumps – 2 in. Polypropylene

## Series 1542P



1542P-65SPM 6.5 HP with frame

- Gas engine driven (EPA & CARB certified-North America and EC/CE Listed -Europe)
- Pump Seals: EPDM Mechanical
- Suction lift: 25 ft./7.62 m
- Available with or without frame

### Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Port Size	Engine Mfg. & HP
1542P-65SP	200	757	58	4.0	2" x 2" NPT	PowerPro 6.5 hp
1542P-65SPM	200	757	58	4.0	2" x 2" NPT	PowerPro 6.5 hp with frame
1542P-65ESP	200	757	58	4.0	2" x 2" NPT	PowerPro 6.5 hp w/ elec. start
1442P-65SP	200	757	58	4.0	2" x 2" NPT	6.5 HP EC/CE listed
1542P-160HSP	200	757	58	4.0	2" x 2" NPT	Honda® GX160
1542P-200HSP	200	757	58	4.0	2" x 2" NPT	Honda® GX200
1542P-950BSP	200	757	58	4.0	2" x 2" NPT	Briggs & Stratton® 950
1542P-55SP	150	568	58	4.0	2" x 2" NPT	PowerPro 6.5 hp
1542P-550BSP	150	568	58	4.0	2" x 2" NPT	Briggs & Stratton® 550
3410-0041	Cam lock kit					
3430-0690	Pump head kit for 1542P-55SP with EPDM seal					
3430-0691	Pump head kit for 1542P-65SP with EPDM seal					
3430-0635	EPDM seal kit					
3430-0659	Viton seal kit					

### 1542P-55SP, 1542P-550BSP

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 58 PSI
150	147	131	108	80	48	0

### U.S. Units

### 1542P-55SP, 1542P-550BSP

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.0 BAR
568	556	496	409	303	182	0

### Metric Units

### 1542P-65SP, 1542P-200HSP, 1542P-950BSP

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 58 PSI
200	182	162	136	106	65	0

### U.S. Units

### 1542P-65SP, 1542P-200HSP, 1542P-950BSP

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.0 BAR
757	689	613	515	401	246	0

### Metric Units

# Hydraulically-Driven Transfer Pumps – 2 in. Polypropylene

## Series 9342P

9342P-HM\_C-5SP  
Hydraulic drive



### Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Port Size	Motor Capacity
9342P-HM1C-5SP	200	757	58	4.0	2" x 2" NPT	10 gpm
9342P-HM5C-5SP	206	780	60	4.1	2" x 2" NPT	11 gpm
3430-0635	EPDM seal kit					

### 9342P-HM1C-5SP

Hyd. Flow GPM	GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 58 PSI
8	165	145	122	95	57		
9	185	166	144	119	86	0	
10	200	184	164	141	114	80	0

### U.S. Units

### 9342P-HM1C-5SP

Hyd. Flow LPM	LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.0 BAR
30.3	625	549	463	358	215		
34.1	700	630	547	449	325	0	
37.9	757	695	620	534	433	301	0

### Metric Units

### 9342P-HM5C-5SP

Hyd. Flow GPM	GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI
9	175	154	123	84	0		
10	192	174	149	118	76	0	
11	206	189	169	145	117	79	0

### U.S. Units

### 9342P-HM5C-5SP

Hyd. Flow LPM	LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR
34.1	662	582	467	316	0		
37.9	727	658	562	446	288	0	
41.6	780	717	639	550	442	299	0

### Metric Units

Honda® is a registered trademark of Honda Motor Co., Ltd.  
Briggs & Stratton® is a registered trademark of Briggs & Stratton Corporation. Hypro® is a registered trademark of Pentair Ltd.