

# VERSA-TWIN 2130 Series Plunger Pumps



- Molded from Noryl GTX for chemical resistance against fertilizers, insecticides, chlorides, acids, and bleach
- Robust motor, ceramic plunger, and crank drive provide market-leading long life without servicing
- 4-point 1" NPT flynut-ready connections allow for greater flexibility in plumbing, easy installation and servicing, draining and maintenance
- 1" ports allow for single-sided inlet plumbing
- Available in standard models up to 4.0 GPM (15.1 L/min) & 300 PSI (20.7 BAR)

## Order Information

Model Number	Max GPM	Max L/min	Max PSI	Max BAR	Max RPM	Motor Type	Ports
2130P-D183	2.5	9.5	150	10.3	2200	¼ HP 12V DC Motor, 20 amps	1" MNPT
2130P-D355	2.8	10.6	300	20.7	2000	½ HP 12V DC Motor, 35 amps	
2130P-D359	3.9	14.8	200	13.8	2000	½ HP 12V DC Motor, 35 amps	
2130P-D395	2.9	11.0	300	20.7	2000	½ HP 12V DC Motor, 56C, 39 amps	
2130P-D399	4.0	15.1	200	13.8	2000	½ HP 12V DC Motor, 56C, 39 amps	
2130P-A055	2.4	9.1	300	20.7	1750	½ HP 115-208/230V AC Motor, 1 PH 50/60 Hz	
2130P-A079	3.9	14.8	300	20.7	1750	¾ HP 115-208/230V AC Motor, 1 PH 50/60 Hz	
2130PX	Replacement pump head						

## Performance

Model Number	0 PSI / 0 BAR		50 PSI / 3.5 BAR		100 PSI / 6.9 BAR		150 PSI / 10.3 BAR		200 PSI / 13.8 BAR		250 PSI / 17.2 BAR		300 PSI / 20.7 BAR	
	GPM	AMPS	GPM	AMPS	GPM	AMPS	GPM	AMPS	GPM	AMPS	GPM	AMPS	GPM	AMPS
	L / min		L / min		L / min		L / min		L / min		L / min		L / min	
2130P-D183 <sup>1</sup>	2.5	5.2	2.2	9.8	2.0	14.6 *	1.8	19.3 *	-	-	-	-	-	-
	9.5		8.3		7.6		6.8							
2130P-D355 <sup>1</sup>	2.8	9.1	2.5	13.4	2.4	18.9	2.3	23.5	2.2	27.5 *	2.1	30.9 *	2.0	34.8 *
	10.6		9.5		9.1		8.7		8.3		7.9		7.6	
2130P-D359 <sup>1</sup>	3.9	11.6	3.2	17.2	3.1	21.5 *	3.0	26.2 *	2.8	31.8 *	-	-	-	-
	14.8		12.1		11.7		11.4		10.6					
2130P-D395 <sup>1</sup>	2.9	8.3	2.5	13.0	2.4	19.0	2.3	23.5	2.2	27.2	2.1	30.7	2.0	33.9
	11.0		9.5		9.1		8.7		8.3		7.9		7.6	
2130P-D399 <sup>1</sup>	4.0	11.0	3.5	17.2	3.3	24.0	3.1	29.3	3.0	34.2	-	-	-	-
	15.1		13.2		12.5		11.7		11.4					
2130P-A055 <sup>2</sup>	2.4	6.5	2.2	6.6	2.1	6.7	2.1	6.8	2.0	7.0	1.9	7.2	1.9	7.3
	9.1		8.3		7.9		7.9		7.6		7.2		7.2	
2130P-A079 <sup>2</sup>	3.9	8.9	3.4	9.0	3.3	9.1	3.2	9.5	3.1	9.8	3.0	10.1	2.9	10.6
	14.8		12.9		12.5		12.1		11.7		11.4		11.0	

\* indicates intermittent duty only <sup>1</sup> Tested at 13.5 VDC <sup>2</sup> Tested at 110 VAC