

Pedestal Mount, Clutch-Driven, Cast Iron & Stainless Steel

Series 9263C-C and 9263S-C



Upgrade Options:

- Increase dry-run and abrasive resistance with Life Guard Seals
 - Life Guard seals are the OEM standard
- Extend pump life with Stainless Steel
 - Fact: Chemical corrosion, pump cavitation, and abrasive wear are key factors in pump life
 - 316 Stainless Steel pumps provide superior chemical corrosion resistance, while maintaining material strength to prolong the life against abrasive wear
 - 316 Stainless Steel resists cavitation pitting of pumps, extending the wear life
 - Drop in replacements for cast iron pumps

Features

- Available in cast iron and 316 stainless steel for extended pump life
- Pedestal mount with DC clutch drive
- Double “A” groove pulley (5”/125 mm diameter)
- Port sizes: 1-1/2” NPT inlet, 1-1/4” NPT outlet
- 220 x 200 universal flange available (U)
- Stainless steel models now available with universal flanges
- Max. fluid temperature: 140°F/60°C
- Impeller: Nylon (standard in cast iron); polypropylene (standard in stainless steel); GTX available
- Pump seals: Cast Iron models – Viton/ceramic standard; Life Guard silicon carbide (B) available; Stainless Steel models – Life Guard silicon carbide standard
- Life Guard seals are the industry standard on OEM equipment
- Amp draw: 45 watts at 12 volts
- Weight: 23 lbs./10.5 kg

For Flanged Connections You Will Also Need:

- Universal Flange Gasket
- Universal Flange Clamp

See page 214 for details

Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Max RPM	Rotation
9263C-C †	140	530	114	7.9	5000	CCW*
9263C-CR	140	530	114	7.9	5000	CW*
9263S-C †	140	530	114	7.9	5000	CCW*
9263S-CR	140	530	114	7.9	5000	CW*
3430-0332	Seal and o-ring repair kit					
3430-0589	Life Guard silicon carbide seal kit					

† Universal Flange (220 x 200) - Add Suffix “U” (i.e.: 9263C-C-U)

Life Guard silicon carbide seal - Add suffix “B” (i.e.: 9263C-CB)

*CCW (counterclockwise) CW (clockwise) are determined when looking at the shaft end.

9263C-C, 9263S-C, 9263C-CR, 9263S-CR, 9263C-C-U, 9263S-C-U

U.S. Units

RPM	10 PSI		20 PSI		40 PSI		60 PSI		80 PSI		100 PSI	
	GPM	HP	GPM	HP	GPM	HP	GPM	HP	GPM	HP	GPM	HP
2400	80	1.9	65	1.8								
3600	105	5.3	105	5.3	92	5.0	50	3.7				
4200	122	8.2	120	7.9	115	7.7	98	7.1	56	5.3		
5000	140	12.6	140	12.6	138	12.6	130	12.2	118	11.6	88	9.9

9263C-C, 9263S-C, 9263C-CR, 9263S-CR, 9263C-C-U, 9263S-C-U

Metric Units

RPM	0.7 BAR		1.4 BAR		2.8 BAR		4.1 BAR		5.5 BAR		6.9 BAR	
	LPM	HP	LPM	HP	LPM	HP	LPM	HP	LPM	HP	LPM	HP
2400	303	1.9	246	1.8								
3600	397	5.3	397	5.3	348	5.0	189	3.7				
4200	462	8.2	454	7.9	435	7.7	371	7.1	212	5.3		
5000	530	12.6	530	12.6	522	12.6	492	12.2	447	11.6	333	9.9