

Hydraulically-Driven Transfer Pumps – 2 in. Cast Iron



9332C-HM_C-SP

- Housing: cast iron
- Pump seals: fluoroelastomer (viton)
- Suction lift: 20 ft. (6 m)
- Flapper valve: EPDM

Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Hyd. Flow GPM	Hyd. Flow LPM	Port Size
9332C-HM1C-SP	170	644	60	4.1	13	49	2" x 2" NPT
9332C-HM5C-SP	170	644	60	4.1	16	60	2" x 2" NPT

9332C-HM1C-SP

U.S. Units

Hyd. Flow GPM	GPM at 0 PSI	GPM at 5 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI
8	150	138	124	88	53	0		
9	160	150	140	113	79	48	0	
10	170	163	155	135	108	77	42	0

9332C-HM1C-SP

Metric Units

Hyd. Flow LPM	LPM at 0.0 BAR	LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR
30	568	522	469	333	201	0		
34	606	567	530	428	229	182	0	
38	643	617	587	511	409	291	159	0

9332C-HM5C-SP

U.S. Units

Hyd. Flow GPM	GPM at 0 PSI	GPM at 5 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI
10	150	138	123	90	55	0		
11	160	150	140	113	79	48	0	
12	170	163	155	135	108	77	42	0

9332C-HM5C-SP

Metric Units

Hyd. Flow LPM	LPM at 0.0 BAR	LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR
38	568	522	466	341	208	0		
42	606	568	530	428	299	182	0	
45	644	617	587	511	409	291	158	0

Electric Motor Mount Transfer Pumps – 2 in. & 3 in. Cast Iron



- Housing: cast iron
- Pump seals: fluoroelastomer (viton)
- Suction lift: 20 ft. (6 m)
- Flapper valve: EPDM

Order Information

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Port Size	NEMA Frame
9732C-SPX*	170	644	42	2.9	2" x 2" NPT	182/184TC
9733C-SPX*	330	1249	60	4.1	3" x 3" NPT	215TC

* Electric Motor not included

9732C-SPX

U.S. Units

GPM at 0 PSI	GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI
170	151	133	113	94	74	52	25	0

9732C-SPX

Metric Units

LPM at 0.0 BAR	LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR
644	572	503	428	356	280	197	95	0

9733C-SPX

U.S. Units

GPM at 0 PSI	GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 45 PSI	GPM at 50 PSI	GPM at 55 PSI	GPM at 60 PSI	GPM at 61 PSI
330	325	320	310	290	265	230	195	163	133	95	50	11	0

9733C-SPX

Metric Units

LPM at 0.0 BAR	LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 3.1 BAR	LPM at 3.4 BAR	LPM at 3.8 BAR	LPM at 4.1 BAR	LPM at 4.2 BAR
1249	1230	1211	1173	1098	1003	871	738	617	503	360	190	42	0

Viton® is a registered trademark of DuPont. Hypro® is a registered trademark of Pentair.