

Flange Mount, Polypropylene

Series 9513P



Upgrade Options:

- Increase dry-run and abrasive resistance with Life Guard Seals
 - Life Guard seals are the OEM standard

Features

- Mounts clockwise rotation (when looking at the shaft end) — for direct mount to gasoline engines
- Shaft: 3/4" (19 mm) hollow, 416 stainless steel
- Port size: 1-1/2" NPT inlet, 1-1/4" NPT outlet
- Max. fluid temperature: 140°F/60°C
- Housing: Polypropylene
- Impeller: Polypropylene
- Flange bolt pattern for 5 hp gas engine
- Pump seals: Viton/ceramic standard; Life Guard silicon carbide (B) available
- Life Guard seals are the industry standard on OEM equipment
- Weight: 19 lbs./8.6 kg

Order Information

| Model Number | Max GPM | Max LPM | Max PSI | Max BAR | Max RPM | PTO Output |
|--------------|-------------------------------------|---------|---------|---------|---------|---|
| 9513P | 91 | 344 | 65 | 4.5 | 3600 | 3/4" hollow keyed stainless steel shaft for direct coupling to 5hp engine |
| 3430-0333 | Seal and o-ring repair kit | | | | | |
| 3430-0590 | Life Guard silicon carbide seal kit | | | | | |

Life Guard silicon carbide seal - Add suffix "B" (i.e.: 9513P-B)

9513P — Based on 5.5 HP HONDA® Engine U.S. Units

| GPM at 0 PSI | GPM at 10 PSI | GPM at 20 PSI | GPM at 30 PSI | GPM at 40 PSI | GPM at 50 PSI | GPM at 60 PSI |
|--------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 92 | 91 | 88 | 81 | 70 | 58 | 42 |

9513P — Based on 5.5 HP HONDA® Engine Metric Units

| LPM at 0.0 BAR | LPM at 0.7 BAR | LPM at 1.4 BAR | LPM at 2.1 BAR | LPM at 2.8 BAR | LPM at 3.4 BAR | LPM at 4.1 BAR |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 348 | 344 | 333 | 307 | 265 | 220 | 159 |