

12/01

Hy-Line PERFORMANCE DATA SHEET



32.08.01.B

SIZE: 32

SEAL TYPES: ALL

POLISH: 0

ROTORS CODE: 8



APPLICATION DATA

MAX INPUT SHAFT TORQUE (lbft) 11.0
 MAX SHAFT RADIAL LOAD (lb) 3.7
 MAX SOFT PARTICLE DIA (in) 0.25
 DISPLACEMENT (cu in/ rev) 2.1
 DISPLACEMENT (US gals / 100 revs) 0.9

PHYSICAL DATA

Hy-Line PUMP (lb) 17.6
 OIL CAPACITY(cu in) 27.5
 HOLD UP VOLUME(cu in) 1.5

TIGHTENING TORQUES (lbft)

END COVER BOLTS 11.0
 ROTOR RETAINER SCREWS 13.0
 ROTOR CASE SCREWS 6.0
 GEAR COVER SCREWS 6.0
 GEAR NUTS 30.0

ROTOR CLEARANCES (in)

FRONT, ROTOR TO END COVER 0.0016
 RADIAL, ROTOR TO ROTOR CASE 0.0024
 MESH, LOBE TO LOBE - MIN 0.0024

Jabsco



USA
 Jabsco
 20 ICON
 Foothill Ranch
 CA 92610

Tel: +1 949 859-4945
 Fax: +1 949-859-1153

UK
 Jabsco
 Bingley Road
 Hoddesdon
 Hertordshire, EN11 0BU

Tel: +44 (0) 1992 450 145
 Fax: +44 (0) 1992 467 132

GERMANY
 Jabsco GmbH
 Oststraße 25
 22844 Norderstedt

Tel: +49 (0) 40 535 373-0
 Fax: +49 (0) 40 535 373-11