

23250-0000

Features:

- Improves all multiple outlet pressure controlled water systems.
- Approximately 11 litre store of pressurised water. Maintains full flow when system demand temporarily exceeds pump capacity.
- Gives smoother flow, quieter water systems.
- Provides better control of hot water temperature.
- Results in longer pump life, lower battery drain.
- Integral rubber membrane eliminates maintenance and allows universal mounting.
- Integral mounting platform for water pressure pump.



Specifications

Connections: 3/4" BSP female thread.

Volume: 22 Litre (5 gallons).

Working pressure: 10 bar (140 psi) maximum.

Dimensions: 30cm high x 27cm wide x 59cm long (12" x 10" x 23").

Net weight: 5.6 kg (12 1/4 lb).

Ordinary air may be used if it is necessary to increase the pressure. Replace the valve cap securely.

2. MOUNTING

The tank may be mounted in any axis without affecting its performance.

3. LOCATION

The tank should be connected to the outlet line from the water pump, using a "tee" piece in the line. The "tee" piece should be located before the outlet line divides to serve the hot water heater or other outlets. A short run of pipe may be used to connect the "tee" piece to the tank to allow it to be located in a convenient position but the total pipe run from the pump to the tank should be as short as possible.

4. SEALING

A good grade sealant or PTFE tape must be used on the 3/4" threaded male outlet to ensure a water and pressure tight connection.

Installation Instructions

1. SETTING THE PRESSURE

The pressure must be adjusted before mounting the tank, which is delivered already pressurised with NITROGEN.



CAUTION - Nitrogen can cause oxygen starvation, ensure adequate ventilation.

Do not adjust the pressure in a confined space

Unscrew the valve cap to expose the valve. Using a pressure gauge, reduce the pressure to 0.2 bar (3 psi) below the pump cut-in pressure.

Jabsco

Jabsco, 20 Icon, Foothill Ranch, CA 92610

Tel : + 1 949 609 5106 Fax : +1 949 859 1254

Jabsco, Bingley Road, Hoddesdon, Hertfordshire, EN11 0BU

Tel : +44 (0) 1992 450 145 Fax : +44 (0) 1992 467 132

Fluid Products Canada, 55 Royal Road, Guelph, Ontario N1H 1T1

Tel : +1 519 821 1900 Fax : +1 519 821 5316

NHK Jabsco Co Ltd, 3-21-10, Shin - Yokohama, Kohoku-ku, Yokohama 222

Tel : +81 (0) 45 475 8906 Fax : +81 (0) 45 475 8908

Jabsco GmbH, Oststraße 28, 22844 Norderstedt

Tel : +49 (0) 40 53 53 73 0 Fax : +49 (0) 40 53 53 73 11

USA

UK

CANADA

JAPAN

GERMANY

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.