



# JabSCO VeraFlex™

## FLEXIBLE IMPELLER PUMP CART SYSTEM



*The new JabSCO VeraFlex Flexible Impeller Pump Cart System is motorized, includes a wireless remote, and is designed for use throughout the food, dairy, beverage, and industrial markets.*

This is a complete, cost effective solution, offering up to 60 GPM (228 LPM) (with Variable Frequency Drive), while incorporating gentle pumping action to carefully handle thin, viscous, and particle laden fluids.

The new JabSCO cart mounted pump with Variable Frequency Drive (VFD) adjusts the speed of an electric motor by regulating the power being delivered. Variable-frequency drives provide continuous control, matching motor speed to the specific demands of the work being performed.

### Typical Applications

- Ingredients unloading and transfer
- Tank filling and emptying
- Recirculation and mixing
- Portion and container filling
- Sampling and filtration

### Features and Benefits


- Inexpensive to purchase, use, and service
- True self-priming, even from dry startup
- Gentle pumping action with bidirectional flow (reversible)
- Positive displacement to pump and meter viscous fluids
- Hygienic body in 316 stainless steel for easy cleaning
- Washdown Motor



*Engineered for life*

- With over six millions pumps in service, Jabsco is the largest producer of Flexible Impeller pumps in the world.
- Since 1962, Jabsco has offered the most versatile, multi-use pump for wine processing applications, including pump-overs, must transfers, and handling of solids without damage to grape pulp.
- For the past 40 years, Jabsco Flexible Impeller pumps have gently glazed over 2 Million donuts for coffee shops and bakeries, worldwide.

**Flow Curve**



**Specifications**

Pump Type	Close Coupled, 3A
Body	316 Grade Stainless Steel
Impeller	Sanitary Neoprene
Shaft Seal	Mechanical; Carbon-on-Ceramic
Ports	2" Tri-clamp type
Shaft	316 Grade Stainless Steel
Motor	50Hz, 3 HP 112 IEC Frame, Washdown rated, 230 VAC 3 Phase
Variable Frequency Drive	230 VAC 1 Phase input, 50 / 60 Hz
Wireless Remote	Operates on standard 9 VDC battery
Weight	30.0 lb (13.6 kg) Approx Pump Head
Weight	159 lb (72 kg) Approx. Close Coupled

**Wireless Remote Control Features**



- Forward and Reverse operation
- Increase or Decrease Flow
- Red LED fault-detection light
- Wireless RF technology offers up to 50-foot range
- Operates the cart's Variable Frequency Drive (VFD)
- Water-resistant design with rugged rubberized holder

**Variable Frequency Drive (VFD)**



Variable Frequency Drives are an excellent choice for adjustable-speed drive users because they allow operators to fine-tune processes while reducing costs for energy and equipment maintenance.

Four Wheel Cart Variants	No Cart Variants	Cart Part Number	Remotes
52800-1105 - No Remote 52800-2105 - Wired Remote 52800-3105 - Wireless Remote	52800-4105 - Pump Head, Flange, Motor 52800-5105 - Pump Head Flange, Motor, VFD	52804-1000 - 4 Wheel	52805-1000 - Wired 52806-1000 - Wireless

[www.Jabsco.com](http://www.Jabsco.com)

**USA**  
ITT Corporation  
666 Dyer Road  
Santa Ana, California 92705  
Tel: (714) 557 4700  
Fax: (714) 628 8478

**UK**  
ITT Industries  
Bingley Road, Hoddesdon  
Hertfordshire EN11 0BU  
Tel: +44 (0) 1992 450145  
Fax: +44 (0) 1992 467132

**GERMANY**  
ITT Corporation  
Oststrasse 28  
22844 Norderstedt  
Tel: +49-40-53 53 73-0  
Fax: +49-40-53 53 73-11

**CHINA**  
ITT Corporation  
30/F, Tower AHongqiao City Center of  
Shanghai 100 Zunyi Road, Shanghai  
200051, China  
Tel: +(86) 21 2208 2888  
Fax: +(86) 21 2208 2999

**ITALY**  
ITT Corporation  
Via Tommaseo, 6  
20059 Vimercate, Milano  
Tel: +39 039 685 2323  
Fax: +39 039 666 307

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.