

HIGH SPEED

COMPLETE RANGE OF DIESEL TRANSFER AND REFUELLING PUMPS

UP2



UP3

UP4



UP6



UP12



Self-priming electric pumps of small dimensions with bronze gears for transferring of liquids. Pump body in nickel-plated brass and stainless steel shaft. Main applications: transfer of diesel fuel, antifreeze.

TYPE	PART NUMBER	VOLTS	SELF-PRIM.	PRESSURE	FLOW RATE	CONSUMPTION	FUSE	PORTS male
UP2	M164-200-12	12	4,9 ft	22 psi	2,6 gpm	2,8A ÷ 3,2A	5A	3/8" NPT
	M164-200-13	24	4,9 ft	22 psi	2,6 gpm	1,4A ÷ 1,6A	3A	3/8" NPT
UP3	M164-000-12	12	4,9 ft	29 psi	4 gpm	5A ÷ 6A	10A	3/8" NPT
UP4	M164-000-13	24	4,9 ft	29 psi	4 gpm	3A ÷ 4A	5A	3/8" NPT
UP6	M164-060-12	12	4,9 ft	29 psi	6,87 gpm	9A ÷ 11A	15A	1/2" NPT
	M164-060-13	24	4,9 ft	29 psi	6,87 gpm	5A ÷ 6A	7,5A	1/2" NPT
UP12	M164-300-12	12	13,1 ft	36 psi	10,5 gpm	20A	30A	1/2" NPT
	M164-300-13	24	13,1 ft	36 psi	10,5 gpm	11A	15A	1/2" NPT