

[METRIC]

\* STANDARD / SHOWN

PORTS	
A	B
*ACME	9.38" [238.25]
NPT	10.25" [260.35]
BSPP	10.25" [260.35]
CLAMP	9.38" [238.25]
RJT	9.76" [247.90]

FOOT / RISER										
C	D	E	F	G	H	I	J	K	L	
*D33-838	6.44" [163.45]	12.31" [312.67]	7.47" [189.84]	8.75" [222.25]	2.05" [52.16]	7.19" [182.63]	1.76" [44.60]	5.71" [145.03]	8.70" [220.96]	
D33-839	5.97" [151.61]	11.84" [300.84]	10.00" [254]	5.89" [149.61]	3.17" [80.51]	4.33" [109.98]	3.50" [89.90]	8.86" [225.04]	8.23" [209.12]	
P20-154B-18	6.44" [163.45]	12.31" [312.67]	9.62" [244.35]	6.87" [174.50]	4.01" [101.94]	5.23" [132.84]	1.76" [44.60]	7.86" [199.54]	8.70" [220.96]	

BACKPLATE / DRIVESHAFT	
M	N
SAE-A 2 BOLT	1-1/4" KEYED, 25mm KEYED, 1-1/4" 14T SPLINED
SAE-B 2 BOLT	1-1/4" KEYED, 7/8" 13T SPLINED
SAE-B 4 BOLT	1-1/4" KEYED, *1-1/4" 14T SPLINED
MALE	1-3/8" MALE SHAFT

PROPRIETARY NOTICE: THIS DOCUMENT CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION WHICH IS THE EXCLUSIVE PROPERTY OF ROPER PUMP COMPANY, COMMERCE, GEORGIA AND SHALL NOT BE COMMUNICATED, DISCLOSED, OR REPRODUCED WITHOUT WRITTEN CONSENT OF MANAGEMENT AND SHALL NOT BE DISCLOSED IN ANY MANNER TO OUTSIDE PARTIES WITHOUT PRIOR WRITTEN CONSENT OF MANAGEMENT.

**CERTIFIED DIMENSIONALLY CORRECT FOR:**

CUSTOMER  
CUSTOMER P.O.  
BY

ROPER S.O.  
DATE

DO NOT SCALE  
DIMS IN INCHES (MM)




FIGURE  
SANITARY-DIM

SPEC

TYPE  
1