

SPECIFICATIONS:

MODEL NUMBER: 3000-400

PUMP DESIGN: Flexible Impeller Pump With a 3-Way Switch & 8 Ft. [2.4 M] Cable
With Battery Clips Mounted on a 3.5 Gallons (13.2 Liters) Pail

REVERSIBLE FLOW: Yes

VOLTAGE: 12 VDC Nominal

MOTOR: Permanent Magnet, Thermally Protected

OPERATING PRESSURE: 15 PSI (1.0 Bars) Max.

LIQUID TEMPERATURE: 40 °F to 185 °F Max. [4 °C to 85 °C] Oil Should Be
Heated to 140 °F to 160 °F [60 °C to 71 °C] For Max. Pump Efficiency

PRIMING: Pre-Lube Inlet Prior to Pump Operation

MATERIAL OF CONSTRUCTION: (PUMP ONLY)

PLASTICS- Glass Filled Polyester

IMPELLER- Buna-n

LIP SEAL- Buna-n

FASTENERS- Stainless Steel

NET WEIGHT: 6.2 Lbs (2.8 Kg)

OVERALL DIMENSIONS: Height 16" (406 mm), Diameter 12-1/2" (318 mm)

DUTY CYCLE: Intermittent

AGENCY CERTIFICATION: None

TYPICAL APPLICATIONS: General Purpose Oil Changer Pump

