




SHALLOW WELL JET PUMPS



MODEL 2810E 3/4 HP MODEL 2805E 1/2 HP

- Maximum flow 3/4 HP 12.5 gallons per minute
- Maximum flow 1/2 HP 6.9 gallons per minute
- Superior performance at depths to water of 25' or less
- Rugged cast iron construction maximizes pump life
- 3/4 HP ready-to-install heavy-duty dual-voltage motor preset at 230 volts
- 1/2 HP ready-to-install heavy-duty dual-voltage motor preset at 115 volts
- Self-priming after pump housing is initially filled. Protects against over-heating.
- 1-1/4" NPT suction and 1" NPT discharge pipe size



PERFORMANCE

| Model | HP | Warranty | Voltage | Pressure Switch | | GPM Pumped at Different Depths to Water* | | | | | Pressure Shut-off |
|-------|-----|----------|---------|-----------------|-----|--|------|------|-----|-----|-------------------|
| | | | | On | Off | 5' | 10' | 15' | 20' | 25' | |
| 2810E | 3/4 | 1-year | 115/230 | 30 | 50 | 12.5 | 11.4 | 10.1 | 8.2 | 6.8 | 70 PSI |
| 2805E | 1/2 | 1-year | 115/230 | 30 | 50 | 6.9 | 6.0 | 5.3 | 4.5 | 4.0 | 69 PSI |

*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well.

ORDERING INFORMATION

| Model | UPC | Carton (L x W x H) | Cube | Pallet Qty. | Weight |
|-------|-----------------|-----------------------------|-------|-------------|-----------|
| 2810E | 0 17561 15102 7 | 21.688" x 10.688" x 13.563" | 1.819 | 24 | 43.3 lbs. |
| 2805E | 0 17561 14102 8 | 21.688" x 10.688" x 13.563" | 1.819 | 24 | 41.0 lbs. |