




# CONVERTIBLE JET PUMPS



**MODEL 3310P 1 HP**  
**MODEL 3307P 3/4 HP**  
**MODEL 3305P 1/2 HP**

- Superior performance at depths to water of 100' or less
- Fiberglass reinforced thermoplastic pump housing for the highest corrosion resistance
- Ready to install heavy-duty dual-voltage motor preset at 230 volts for 3/4 and 1 HP models preset at 115 volts for 1/2 HP model
- Energy efficient motor
- Self-priming after pump housing is initially filled, check valve or foot valve required
- Pressure switch preset to 30-50 PSI



### PERFORMANCE – Shallow Well of 25 Feet or Less

Model	HP	Warranty	Voltage	Amps	Pressure Switch		GPM Pumped at Different Depths to Water*					Pressure Shut-off
					On	Off	5'	10'	15'	20'	25'	
3310P	1	1-year	115/230	14.8/7.4	30	50	20.7	18.3	15.8	12.3	8.5	52 PSI
3307P	3/4	1-year	115/230	12.2/6.1	30	50	15.3	13.8	11.8	9.2	6.8	52 PSI
3305P	1/2	1-year	115/230	9.4/4.7	30	50	9.0	7.8	6.6	5.7	4.3	62 PSI

### PERFORMANCE – Deep Well With 4" Diameter Casing or Larger

Model	GPM Pumped at Different Depths to Water*											Pressure Shut-off
	20'	25'	30'	40'	50'	60'	70'	80'	90'	100'	110'	
3310P	9	8.8	8.4	7.3	6.2	5	4.4	2.9	2	–	–	56 PSI
3307P	7.5	7.1	6.5	5.1	4	3	2.5	1.8	1.5	1	–	56 PSI
3305P	5.9	5.4	4.5	3.5	2.8	2.3	1.7	–	–	–	–	54 PSI

\*All performances shown in gallons per minute at 40 PSI (pound per square inch) discharge pressure at top of well. FP4800 jet kit sold separately.

### ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
3310P	0 22315 32428 2	21.063" x 12.313" x 12.375"	1.857	18	30.40 lbs.
3307P	0 22315 32427 5	21.063" x 12.313" x 12.375"	1.857	18	27.7 lbs.
3305P	0 22315 32426 8	21.063" x 12.313" x 12.375"	1.857	18	24.4 lbs.