


Model 00L



Iron Construction

Standard Clearance



1/2" Std. Port Size





Viscosity: 32 SSU




Viscosity: 100 SSU



Viscosity: 200 SSU



Viscosity: 500 SSU



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.


Created on November 30, 2000

Model 00L



Iron Construction

Standard Clearance



1/2" Std. Port Size





Viscosity: 32 SSU




Viscosity: 100 SSU



Viscosity: 200 SSU



Viscosity: 500 SSU




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 00L



Iron Construction

Standard Clearance



1/2" Std. Port Size




Viscosity: 1,000 SSU



Viscosity: 5,000 SSU



Viscosity: 10,000 SSU




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 0L



Iron Construction

Standard Clearance



1/2" Std. Port Size





Viscosity: 32 SSU




Viscosity: 100 SSU



Viscosity: 200 SSU



Viscosity: 500 SSU




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 0L



Iron Construction

Standard Clearance



1/2" Std. Port Size




Viscosity: 1,000 SSU



Viscosity: 5,000 SSU



Viscosity: 10,000 SSU




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 1L



Iron Construction

Standard Clearance



1/2" Std. Port Size





Viscosity: 32 SSU




Viscosity: 100 SSU



Viscosity: 200 SSU



Viscosity: 500 SSU




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 1L



Iron Construction

Standard Clearance



1/2" Std. Port Size




Viscosity: 1,000 SSU



Viscosity: 5,000 SSU



Viscosity: 10,000 SSU




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 2L



Iron Construction

Standard Clearance



1/2" Std. Port Size





Viscosity: 32 SSU




Viscosity: 100 SSU



Viscosity: 200 SSU



Viscosity: 500 SSU






There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 2L

Iron Construction

Standard Clearance

1/2" Std. Port Size




There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Model 5L



Iron Construction

Standard Clearance



1" Std. Port Size





Viscosity: 32 SSU




Viscosity: 100 SSU



Viscosity: 200 SSU



Viscosity: 500 SSU



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.


Created on November 30, 2000

Model 5L



Iron Construction

Standard Clearance



1" Std. Port Size





Viscosity: 1,000 SSU




Viscosity: 5,000 SSU



Viscosity: 10,000 SSU



Viscosity: 25,000 SSU



There are many additional factors to consider when selecting a pump, including (but not limited to) suction conditions, temperature limitations and material compatibilities. Curve data is typical only, actual performance may vary. Consult the factory or an authorized Tuthill Pump Group representative for assistance.

Created on November 30, 2000

Tuthill Pump Group

12500 S. Pulaski Road, Alsip, IL 60803

www.tuthillpump.com

Excellence at work. Excellence in life.