

**BIODIESEL FUEL TRANSFER PUMPS**



Fill-Rite's line of biodiesel compatible fuel transfer pumps make it possible to pump today's alternative fuel – biodiesel (B21 to B100) with the same accuracy, durability and reliability you've come to expect from Fill-Rite. DC and AC models are available to meet most application needs.

**H Heavy Duty**  
Two Year Warranty

**BIODIESEL**  
B21 to B100 Compatible  
Must meet ASTM D6754 Standards



Model BD1210C Up to 15 GPM

DC Rotary Vane Biodiesel Pump  
Series BD1200C



Model BD4210D Up to 20 GPM

DC High Flow Biodiesel Pump  
Series BD4200D



Model BD700 Up to 20 GPM

AC Utility Rotary Vane Biodiesel Pump  
Series BD700



Model BD310 Up to 35 GPM

AC Utility High Flow Rotary Vane  
Biodiesel Pump  
Series BD310



Model BD807CMK

3-Wheel Mechanical Biodiesel Meter  
Series BD800



Model BD901MK

4-Wheel Mechanical Biodiesel Meter  
Series BD900



8825 Aviation Drive  
Fort Wayne, Indiana USA 46809  
Tel 260 747-7524 Fax 260 747-3159  
www.tuthill.com

**Manufacturer of Quality:**  
Hand Pumps • DC/AC Fuel Pumps • Flow Meters • Cabinet Pumps

<b>Biodiesel Fuel Transfer Pumps</b>	<b>Series BD1200C</b>	<b>Series BD4200D</b>	<b>Series BD700</b>	<b>Series BD310</b>
<b>Features</b>	<b>12 Volt DC Rotary Vane Pump</b>	<b>12 Volt Dc High Flow Pump</b>	<b>115 Volt AC High Flow Pump</b>	<b>115 Volt Super High Flow Pump</b>
Warranty	2 years	2 years	2 years	2 years
Construction – pump housing	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Maximum flow rate with factory-provided hose and nozzle	Up to 15 GPM (57 LPM)	Up to 20 GPM (76 LPM)	Up to 20 GPM (76 LPM)	Up to 3/4 HP: 35 GPM (132 LPM)
Rotor composition	Iron	Iron	Iron	Iron
Explosion-proof motor with 2 sealed ball bearings	1/4 HP	1/4 HP	1/3 HP	3/4 HP
Amp draw from battery	20 Amp	22 Amp		
AC/hertz	—	—	115 volt - 60Hz	Dual Voltage 115/230 VAC 50-60Hz
Thermal overload protection	Yes	Yes	Yes	Yes
Inlet	1" NPT	1" NPT	1" NPT	1 1/2" NPT
Outlet	3/4" NPT	1" NPT	3/4" NPT	1" NPT
Tank adapter	2" NPT	2" NPT	2" NPT	2" NPT
Pump may be padlocked	Yes	Yes	Yes	Yes
Machined carbon vanes	Yes	Yes	Yes	Yes
Duty cycle	30 minute	30 minute	30 minute	30 minute
Internal bypass valve	Yes	Yes	Yes	Yes
Built-in strainer	Yes	Yes	Yes	Yes
Nozzle hanger to protect from dirt	Yes	Yes	Yes	Yes
Integral check valve	—	—	Yes	Yes

#### Available Options

Series 800 biodiesel meter	Yes	—	Yes	—
Series 900 biodiesel meter	—	Yes	—	Yes
Automatic nozzle	Yes	Yes	Yes	Yes
Pedestal for underground tanks	—	—	Yes	Yes

#### Box Contents

Hose with static wire	3/4" x 12' (3.7m)	1" x 12' (3.7m)	3/4" x 12' (3.7m)	1" x 12' (3.7m)
Nozzle	1" manual w/reducer bushing	1" manual	1" manual w/reducer bushing	1" manual
Telescoping steel suction pipe – 1" NPT	Yes	Yes	—	—
18' (4.6m) 3-wire power cable	Yes	Yes	—	—

#### Applications

Compatible fluids	B21 to B100 biodiesel fuel only	B21 to B100 biodiesel fuel only	B21 to B100 biodiesel fuel only	B21 to B100 biodiesel fuel only
Minimum operating temperature	40°F	40°F	40°F	40°F

<b>Meters</b>	<b>Series BD800</b>	<b>Series BD900</b>
<b>Features</b>	<b>3 Wheel Mechanical Flow Meter</b>	<b>4 Wheel Mechanical Flow Meter</b>
Accuracy	±1%	±2%
Flow rate	5 to 20 GPM (19 to 76 LPM)	6 to 40 GPM (23 to 151 LPM)
Pressure rating (PSI)	50 (3.4 bar)	50 (3.4 bar)
Resettable cumulative totalizer	99.9 Gallons / 999 Liter	999.9 Gallon / 9999 Liter
Master totalizer	99,999.9 Gallons / 999999 Liter	999,999.9 Gallons / 9999999 Liter
Construction	Aluminum	Aluminum
Large easy to read numbers	Yes	Yes

#### Available Options

Gallon	Yes	Yes
Inlet/outlet ports	3/4" outlet	1" outlet (inlet castings for BD4210D and BD310 included)

#### Applications

Compatible fluids	B21 to B100 biodiesel fuel only	B21 to B100 biodiesel fuel only
-------------------	---------------------------------	---------------------------------



8825 Aviation Drive  
Fort Wayne, Indiana USA 46809  
Tel 260 747-7524 Fax 260 747-3159  
www.tuthill.com