



# 3-Wire, 4" Submersible Well Pumps



**For Residential Water Systems  
or Agricultural Applications**

Pumps to depth of 400'

**High Performance**

Proven floating stack impeller design for sand resistance and reduced sand locking

**Durable Construction**

Stainless steel pump and motor housing



**Control Box Included**

**1/2 HP – 1 HP 14-26.2 GPM**

PERFORMANCE																	
MODEL/ UPC	HP	GPM SERIES	VOLTS	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER IN FEET											DISCHARGE	CARTON DIMS. (IN INCHES)	WEIGHT (LBS.)
				20'	40'	60'	80'	100'	150'	200'	250'	300'	350'	400'			
<b>FP3212</b> 022315101944	<b>1/2</b>	<b>10</b>	230	13.2	12.2	10.9	9.6	8.1	2	-	-	-	-	-	1-1/4"	21 x 12.5 x 12.3	25
<b>FP3222</b> 022315101951	<b>3/4</b>	<b>10</b>	230	14.8	14.2	13.4	12.6	11.7	8.8	5.2	-	-	-	-	1-1/4"	6 x 4.6 x 40	28
<b>FP3232</b> 022315101968	<b>1</b>	<b>10</b>	230	-	-	14.7	14	13.4	11.7	9.7	7.3	4.4	-	-	1-1/4"	6 x 4.6 x 40	31
<b>FP3242</b> 022315100916	<b>1-1/2</b>	<b>10</b>	230	-	-	-	-	14.9	13.8	12.5	11.2	10.4	7.9	5.8	1-1/4"	6 x 4.5 x 49	41
<b>FP3332</b> 022315101975	<b>1</b>	<b>20</b>	230	27	24.5	22.0	19.4	16.8	2.6	-	-	-	-	-	1-1/4"	5 x 4.5 x 43.5	30
<b>FP3342</b> 022315163294	<b>1-1/2</b>	<b>20</b>	230	-	-	26.2	24.3	22.3	17.3	8	-	-	-	-	1-1/4"	48.9 x 5.8 x 4.6	41

\*All performances shown in gallons per minute at 40 PSI discharge pressure at the top of the well.

**Optimal pump performance**

Includes: Control box