

Gas Engine-Driven Transfer Pumps – 2 in. & 3 in. Cast Iron

Series 1530



1532C-6SP with PowerPro Engine

- Gas engine driven (EPA & CARB certified)
- Pump seals: fluoroelastomer (viton)
- Suction lift: 20 ft. (6 m)
- Flapper valve: EPDM

Order Information

| Model Number | Max GPM | Max LPM | Max PSI | Max BAR | Port Size | Engine Mfr. & HP |
|---------------|---------|---------|---------|---------|---|----------------------------------|
| 1532C-6SP | 170 | 644 | 42 | 2.9 | 2" x 2" NPT | PowerPro 6.5 hp |
| 1532C-160HSP | 170 | 644 | 42 | 2.9 | 2" x 2" NPT | Honda GX160 |
| 1533C-13SP | 330 | 1249 | 60 | 4.1 | 3" x 3" NPT | PowerPro 13 hp |
| 1533C-13ESP | 330 | 1249 | 60 | 4.1 | 3" x 3" NPT | PowerPro 13 hp w/ electric start |
| 1533C-390EHSP | 330 | 1249 | 60 | 4.1 | 3" x 3" NPT | Honda GX390 w/ electric start |
| 3430-0673CSP | 170 | 644 | 42 | 2.9 | Pump head kit for 2" NPT self-priming cast iron transfer pump | |
| 3430-0674CSP | 330 | 1249 | 60 | 4.1 | Pump head kit for 3" NPT self-priming cast iron transfer pump | |

1532C-6SP, 1532C-160HSP

U.S. Units

| GPM at 0 PSI | GPM at 5 PSI | GPM at 10 PSI | GPM at 15 PSI | GPM at 20 PSI | GPM at 25 PSI | GPM at 30 PSI | GPM at 35 PSI | GPM at 40 PSI | GPM at 42 PSI |
|--------------|--------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 170 | 155 | 140 | 123 | 106 | 87 | 65 | 42 | 14 | 0 |

1532C-6SP, 1532-160HSP

Metric Units

| LPM at 0.0 BAR | LPM at 0.3 BAR | LPM at 0.7 BAR | LPM at 1.0 BAR | LPM at 1.4 BAR | LPM at 1.7 BAR | LPM at 2.1 BAR | LPM at 2.4 BAR | LPM at 2.8 BAR | LPM at 2.9 BAR |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 644 | 587 | 530 | 466 | 401 | 329 | 246 | 159 | 53 | 0 |

1533C-13SP, 1533C-13ESP, 1533C-390EHSP

U.S. Units

| GPM at 0 PSI | GPM at 5 PSI | GPM at 10 PSI | GPM at 15 PSI | GPM at 20 PSI | GPM at 25 PSI | GPM at 30 PSI | GPM at 35 PSI | GPM at 40 PSI | GPM at 45 PSI | GPM at 50 PSI | GPM at 60 PSI | GPM at 66 PSI |
|--------------|--------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 330 | 325 | 321 | 315 | 296 | 273 | 248 | 221 | 192 | 161 | 129 | 48 | 0 |

1533C-13SP, 1533C-13ESP, 1533C-390EHSP

Metric Units

| LPM at 0.0 BAR | LPM at 0.3 BAR | LPM at 0.7 BAR | LPM at 1.0 BAR | LPM at 1.4 BAR | LPM at 1.7 BAR | LPM at 2.1 BAR | LPM at 2.4 BAR | LPM at 2.8 BAR | LPM at 3.1 BAR | LPM at 3.4 BAR | LPM at 4.1 BAR | LPM at 4.6 BAR |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 1249 | 1230 | 1215 | 1192 | 1120 | 1033 | 938 | 836 | 726 | 609 | 488 | 181 | 0 |

Pedestal-Mount Transfer Pumps – 2 in. & 3 in. Cast Iron



3430-0674CSP



9232C-SP

Order Information

| Model Number | Max GPM | Max LPM | Max PSI | Max BAR | Description |
|--------------|--|---------|---------|---------|---|
| 9232C-SP | 170 | 644 | 42 | 2.9 | 2" x 2" NPT self priming pedestal-mount cast iron transfer pump |
| 9233C-SP | 330 | 1249 | 60 | 4.1 | 3" x 3" NPT self priming pedestal-mount cast iron transfer pump |
| 3430-0673CSP | 170 | 644 | 42 | 2.9 | Pump head kit for 2" NPT self-priming cast iron transfer pump |
| 3430-0674CSP | 330 | 1249 | 60 | 4.1 | Pump head kit for 3" NPT self-priming cast iron transfer pump |
| 3430-0675 | Replacement pedestal for 2" NPT self-priming cast iron transfer pump | | | | |
| 3430-0676 | Replacement pedestal for 3" NPT self-priming cast iron transfer pump | | | | |

9232C-SP, 3430-0673CSP

U.S. Units

| GPM at 0 PSI | GPM at 5 PSI | GPM at 10 PSI | GPM at 15 PSI | GPM at 20 PSI | GPM at 25 PSI | GPM at 30 PSI | GPM at 35 PSI | GPM at 40 PSI | GPM at 42 PSI |
|--------------|--------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 170 | 155 | 140 | 123 | 106 | 87 | 65 | 42 | 14 | 0 |

9232C-SP, 3430-0673CSP

Metric Units

| LPM at 0.0 BAR | LPM at 0.3 BAR | LPM at 0.7 BAR | LPM at 1.0 BAR | LPM at 1.4 BAR | LPM at 1.7 BAR | LPM at 2.1 BAR | LPM at 2.4 BAR | LPM at 2.8 BAR | LPM at 2.9 BAR |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 644 | 587 | 530 | 466 | 401 | 329 | 246 | 159 | 53 | 0 |

9233C-SP, 3430-0674CSP

U.S. Units

| GPM at 0 PSI | GPM at 5 PSI | GPM at 10 PSI | GPM at 15 PSI | GPM at 20 PSI | GPM at 25 PSI | GPM at 30 PSI | GPM at 35 PSI | GPM at 40 PSI | GPM at 45 PSI | GPM at 50 PSI | GPM at 60 PSI | GPM at 66 PSI |
|--------------|--------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 330 | 325 | 321 | 315 | 296 | 273 | 248 | 221 | 192 | 161 | 129 | 48 | 0 |

9233C-SP, 3430-0674CSP

Metric Units

| LPM at 0.0 BAR | LPM at 0.3 BAR | LPM at 0.7 BAR | LPM at 1.0 BAR | LPM at 1.4 BAR | LPM at 1.7 BAR | LPM at 2.1 BAR | LPM at 2.4 BAR | LPM at 2.8 BAR | LPM at 3.1 BAR | LPM at 3.4 BAR | LPM at 4.1 BAR | LPM at 4.6 BAR |
|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| 1249 | 1230 | 1215 | 1192 | 1120 | 1033 | 938 | 836 | 726 | 609 | 488 | 181 | 0 |