

Pedestal Mount, Cast Iron

Series 9208



Features

- 5" ANSI-flanged inlet x 4" ANSI-flanged outlet
- 316 stainless steel impeller for superior corrosion resistance
- 9208 version includes a solid 416 stainless steel shaft for corrosion resistance
- The 9208 shaft diameter is 1.63" (41.3 mm) to allow direct coupling to electric motors
- Life Guard silicon carbide seal for premium abrasion resistance and dry run protection
- Life Guard seals are the industry standard on OEM equipment
- Pump shaft rotation: Counter clockwise when looking at the shaft end

Order Information

| Model Number | Max GPM | Max LPM | Max PSI | Max BAR | Max RPM | Shaft Output |
|--------------|-------------------------------------|---------|---------|---------|---------|--|
| 9208C | 1400 | 5300 | 85 | 5.9 | 3000 | 1-5/8" (41.3 mm) solid keyed Stainless Steel shaft |
| 3430-0604 | Life Guard silicon carbide seal kit | | | | | |

9208C

U.S. Units

| RPM | 20 PSI | | 40 PSI | | 60 PSI | |
|------|--------|------|--------|------|--------|------|
| | GPM | HP | GPM | HP | GPM | HP |
| 1750 | 607 | 10.8 | | | | |
| 2500 | 1071 | 32.3 | 852 | 31.0 | 474 | 24.4 |
| 2750 | 1052 | 38.5 | 1027 | 42.0 | 788 | 38.2 |

9208C

Metric Units

| RPM | 1.4 BAR | | 2.8 BAR | | 4.1 BAR | |
|------|---------|------|---------|------|---------|------|
| | LPM | HP | LPM | HP | LPM | HP |
| 1750 | 2298 | 10.8 | | | | |
| 2500 | 4054 | 32.3 | 3225 | 31.0 | 1794 | 24.4 |
| 2750 | 3982 | 38.5 | 3888 | 42.0 | 2983 | 38.2 |