

Gas Engine-Driven, Medium Pressure, 2 Diaphragm

Model: D30HRGI-65, D30HRGI-65E, D30GRGI-65, 1535, D30HRGI



- Closed-coupled, gas engine driven (EPA & CARB certified)
- Max. fluid temperature: 140°F/60°C
- Diaphragms: 2, semi-hydraulic, Desmopan® standard, Buna available
- Housing components for liquid handling: epoxy-coated

Order Information

| Pressure in PSI and BAR | D30HRGI-65,65E | D30GRGI-65,1535 |
|-------------------------|----------------|-----------------|
| | GPM | GPM |
| | LPM | LPM |
| | @550 RPM | @550 RPM |
| 0 PSI | 9.6 | 9.3 |
| 0 BAR | 36 | 35 |
| 290 PSI | 8.8 | 9.3 |
| 20 BAR | 33 | 34 |
| 435 PSI | 8.6 | 8.7 |
| 30 BAR | 33 | 33 |
| 580 PSI | 8.3 | 8.2 |
| 40 BAR | 31 | 31 |

| Model Number | Max GPM | Max LPM | Max PSI | Max BAR | Max RPM | Control Unit and Gearbox | Engine Mfgr. and hp |
|--------------|---------|---------|---------|---------|---------|------------------------------|---|
| D30HRGI-65 | 9.6 | 36.3 | 580 | 40 | 3600 | GS40GI and 8000-0056 | PowerPro 6.5 HP |
| D30HRGI-65E | 9.6 | 36.3 | 580 | 40 | 3600 | GS40GI and 8000-0056 | PowerPro 6.5 HP w/ electric start |
| D30GRGI-65 | 9.6 | 36.3 | 580 | 40 | 3600 | GS40GI and KIT1640 (gearbox) | PowerPro 6.5 hp |
| 1535 | 9.3 | 35.2 | 580 | 40 | 3600 | GS40GI and KIT1640 (gearbox) | Industrial Plus Briggs & Stratton® 6.5 hp |
| D30HRGI | 9.3 | 35.2 | 580 | 40 | 3600 | GS40GI and KIT1640 (gearbox) | Less engine |

Gas Engine-Driven, Medium Pressure, 3 Diaphragm

Model: D403HRGI-65, D403HRGI-65E, D403GRGI-65, D403HRGI



- Closed-coupled, gas engine driven (EPA & CARB certified)
- Max. fluid temperature: 140°F/60°C
- Diaphragms: 3, semi-hydraulic, Desmopan® standard, Buna available
- Housing: anodized aluminum
- Mounting base: included

Order Information

| Pressure in PSI and BAR | D403HRGI-65,65E | D403GRGI-65 |
|-------------------------|-----------------|-------------|
| | GPM | GPM |
| | LPM | LPM |
| | @550 RPM | @550 RPM |
| 0 PSI | 9.9 | 10.6 |
| 0 BAR | 38 | 40 |
| 290 PSI | 9.7 | 9.8 |
| 20 BAR | 37 | 37 |
| 435 PSI | 9.6 | 9.7 |
| 30 BAR | 36 | 37 |
| 580 PSI | 9.5 | 9.5 |
| 40 BAR | 36 | 36 |

| Model Number | Max GPM | Max LPM | Max PSI | Max BAR | Max RPM | Control Unit and Gearbox | Engine Mfgr. and hp |
|--------------|---------|---------|---------|---------|---------|----------------------------|-----------------------------------|
| D403HRGI-65 | 9.9 | 37.5 | 580 | 40 | 3600 | GR40 and 8000-0056 | PowerPro 6.5 HP |
| D403HRGI-65E | 9.9 | 37.5 | 580 | 40 | 3600 | GR40 and 8000-0056 | PowerPro 6.5 HP w/ electric start |
| D403HRGI | 9.9 | 37.5 | 580 | 40 | 3600 | GR40 and 8000-0056 | Less engine |
| D403GRGI-65 | 10.6 | 40.1 | 580 | 40 | 3600 | GR40 and KIT1640 (gearbox) | PowerPro 6.5 hp |

Desmopan® is a registered trademark of Bayer Aktiengesellschaft, Farbenfabriken. Hypro® is a registered trademark of Pentair.