

Gas Engine-Driven, Medium Pressure, 2 Diaphragm

Model: D30HRGI-65, D30HRGI-65E, D30GRGI-65, 1535, D30HRGI



- Closed-coupled, gas engine driven (EPA & CARB certified)
- Max. fluid temperature: 140°F/60°C
- Diaphragms: 2, semi-hydraulic, Desmopan® standard, Buna available
- Housing components for liquid handling: epoxy-coated

Order Information

Pressure in PSI and BAR	D30HRGI-65,65E	D30GRGI-65,1535
	GPM	GPM
	LPM	LPM
	@550 RPM	@550 RPM
0 PSI	9.6	9.3
0 BAR	36	35
290 PSI	8.8	9.3
20 BAR	33	34
435 PSI	8.6	8.7
30 BAR	33	33
580 PSI	8.3	8.2
40 BAR	31	31

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Max RPM	Control Unit and Gearbox	Engine Mfgr. and hp
D30HRGI-65	9.6	36.3	580	40	3600	GS40GI and 8000-0056	PowerPro 6.5 HP
D30HRGI-65E	9.6	36.3	580	40	3600	GS40GI and 8000-0056	PowerPro 6.5 HP w/ electric start
D30GRGI-65	9.6	36.3	580	40	3600	GS40GI and KIT1640 (gearbox)	PowerPro 6.5 hp
1535	9.3	35.2	580	40	3600	GS40GI and KIT1640 (gearbox)	Industrial Plus Briggs & Stratton® 6.5 hp
D30HRGI	9.3	35.2	580	40	3600	GS40GI and KIT1640 (gearbox)	Less engine

Gas Engine-Driven, Medium Pressure, 3 Diaphragm

Model: D403HRGI-65, D403HRGI-65E, D403GRGI-65, D403HRGI



- Closed-coupled, gas engine driven (EPA & CARB certified)
- Max. fluid temperature: 140°F/60°C
- Diaphragms: 3, semi-hydraulic, Desmopan® standard, Buna available
- Housing: anodized aluminum
- Mounting base: included

Order Information

Pressure in PSI and BAR	D403HRGI-65,65E	D403GRGI-65
	GPM	GPM
	LPM	LPM
	@550 RPM	@550 RPM
0 PSI	9.9	10.6
0 BAR	38	40
290 PSI	9.7	9.8
20 BAR	37	37
435 PSI	9.6	9.7
30 BAR	36	37
580 PSI	9.5	9.5
40 BAR	36	36

Model Number	Max GPM	Max LPM	Max PSI	Max BAR	Max RPM	Control Unit and Gearbox	Engine Mfgr. and hp
D403HRGI-65	9.9	37.5	580	40	3600	GR40 and 8000-0056	PowerPro 6.5 HP
D403HRGI-65E	9.9	37.5	580	40	3600	GR40 and 8000-0056	PowerPro 6.5 HP w/ electric start
D403HRGI	9.9	37.5	580	40	3600	GR40 and 8000-0056	Less engine
D403GRGI-65	10.6	40.1	580	40	3600	GR40 and KIT1640 (gearbox)	PowerPro 6.5 hp

Desmopan® is a registered trademark of Bayer Aktiengesellschaft, Farbenfabriken. Hypro® is a registered trademark of Pentair.