

### SELF-PRIMING PUMPS

#### FEATURES

<b>Body:</b>	Phenolic Plastic
<b>Impeller:</b>	Neoprene, Nitrile or Viton*
<b>Seal:</b>	Lip Type
<b>Ports:</b>	5/8" OD for Hose Connections
<b>Shaft:</b>	Shaft of Motor (Stainless Steel)
<b>Motor:</b>	115 Vac, 1/6 hp, 1750 RPM, 60 Hz, relay start and thermal over-load protector, Three-prong ground plug
<b>Weight:</b>	12 lb (5.4 kg) approx.



Model 12290-Series

MODEL	DESCRIPTION
-------	-------------

<b>12290-0001</b>	Neoprene Impeller; Open Drip Proof Motor
<b>12290-0003</b>	Nitrile Impeller; Open Drip Proof Motor
<b>12290-0004</b>	Viton Impeller and Seal; Open Drip Proof Motor
<b>12290-0271</b>	Neoprene Impeller; Totally Enclosed Motor
<b>12290-0273</b>	Nitrile Impeller; Totally Enclosed Motor
<b>12290-0274</b>	Viton Impeller and Seal; Totally Enclosed Motor

#### APPLICATIONS

Designed as a low cost pump for: transfers, circulation, spill returns, filtration and filling line use. Easily handles pure solutions, foaming liquids, emulsions, suspended solids and ferments with viscosities less than 500 SSU (120 cp). Because the plastic pump is resistant to corrosion and metallic contamination, it is widely used for pumping photo chemicals, plating compounds, lab solutions, pharmaceuticals, cosmetics, weak acids, alkalies, liquid fertilizers, insecticides, dyes, detergents, waxes and many more.

See the Jabsco Chemical Resistance Table in the Industrial Catalog, available upon request from Jabsco, which has been prepared to help you select the most suitable impeller and pump material.

#### OPERATING INSTRUCTION

1. **INSTALLATION** – Pump may be mounted in any position. Intake port is on right when viewing pump end cover.

#### ⚠ WARNING



**Explosion hazard. Motor can spark. Explosion & death can occur. Do not use where flammable vapors are present.**

2. **SELF-PRIMING** – Vertical dry suction lift of up to 10 feet (3 m) for neoprene; 5 feet (1.5 m) for nitrile and viton. Pump will produce suction lift up to 15 feet (4.5 m) when wetted. **BE SURE SUCTION LINES ARE AIRTIGHT OR PUMP WILL NOT SELF-PRIME.**
3. **DISCHARGE LINE** – When transferring liquids further than 25 feet (7.6 m), use 3/4 inch (17.5 mm) discharge line.
4. **RUNNING DRY** – Unit depends on liquid pumped for lubrication. **DO NOT RUN DRY FOR MORE THAN 30 SECONDS.** Lack of liquid will damage the impeller and other pump components.
5. **NOTICE** – When corrosive fluids are handled, pump life will be prolonged if pump is flushed with water after each use or after each work day. For further information, contact factory.
6. **PRESSURES** – For continuous operation, pressure should not exceed 15 psi (1.05 kg/cm).
7. **TEMPERATURES** – Impellers are suitable for service as follows: Neoprene impeller 45° to 180°F (4.4° to 82.2°C), Nitrile impeller 50° to 180°F (10° to 82.2°C) and Viton impeller 60° to 180° F (15.6° to 82.2°C).
8. **SPARE PARTS** – A Jabsco Service Kit should be kept on hand to maintain all but the most badly worn pumps.

\* Viton is a registered trademark of E.I. Du Pont de Nemours and Company.

