



High Pressure Washdown Pump

PAR-MAX SERIES

NEW! Jabsco® High Capacity Washdown Pumps

NEW! High Capacity Washdown Pumps

- Flow rates to 7.5 GPM (29 LPM)
- Pressures up to 80 PSI (5.5 bar)
- Pumpgard™ Intake Strainer and Pressure Nozzle included (suitable for use in salt water)
- Corrosion resistant
- Soft rubber mounts
- Snap-fit port fittings
- 12 and 24 VDC models
- Self priming up to 6 feet (1.8m)
- ISO 8846 MARINE (ignition protection)
- CE



Pressure Nozzle & Pumpgard™ Intake Strainer included

Jabsco now offers boaters the highest capacity Washdown pump on the market today! Jabsco's complete range of Washdown pumps includes models with flows ranging from 3.5 to 7.5 GPM (13-29 LPM). The PAR-Max 6 washdown and the PAR-Max 8 washdown models are new to Jabsco, with pressures up to 80 PSI (5.5 bar). The high capacity performance characteristics match the needs of the larger vessel to wash decks and anchors clean. We include our quick connect 3/4" (19 mm) straight and 90° angled 3/4" (19 mm) hose barbs and QEST 1/2" – 14 straight and 90° angled pipe thread fittings for the 6.0 and 7.5 GPM models for ease of pump installation. All units come with a Pumpgard™ intake strainer, pressure nozzle and 3/4" (19 mm) adapter for nozzle attachment.

Specifications						
	Model (12V)	Amp Draw (A)	Model (24V)	Amp Draw (A)	PSI (bar)	GPM (LPM)
PAR-Max 6	41700-0092	9.0	41700-0094	4.5	80 (5.5)	6.0 (23)
PAR-Max 8	51700-0092	13.5	51700-0094	6.8	80 (5.5)	7.5 (29)

Jabsco





**PAR-Max High Capacity,
High Pressure Washdown Pumps**

PAR-Max 6
41700 Series.....6.0 GPM (23 LPM)
Washdown Pump

PAR-Max 8
51700 Series.....7.5 GPM (29 LPM)
Washdown Pump

Product Features

- Flow rates to 7.5 GPM (29 LPM)
- Pressures up to 80 PSI (5.5 bar)
- Intake Strainer and Pressure Nozzle included
- Corrosion resistant
- Soft rubber mounts
- Snap-fit port fittings
- 12 and 24 VDC models
- Self priming up to 6 feet (1.8m)
- ISO 8846 MARINE (ignition protection)
- CE

Specifications

Materials Pump Body.....Nylon
Diaphragm.....Santoprene
Valves.....EPDM
Switch.....80 PSI (5.5 bar) cut off

Temperature
Water.....Up to 160°F (70°C)

Dimensions PAR-Max 6.....6" H x 6.3" W x 12" L
(152mm x 160mm x 305mm)

PAR-Max 8.....6" H x 6.3" W x 10" L
(152mm x 160mm x 254mm)

Weight PAR-Max 6.....8lb. (3.6 kg)
PAR-Max 8.....9.5lb. (4.3 kg)

Open Flow PAR-Max 6.....6 GPM (23 LPM)
PAR-Max 8.....7.5 GPM (29 LPM)

Typical Operating Pressure
PAR-Max 6/8.....60 PSI (4.1 bar)

Shut-off Pressure
PAR-Max 6/8.....80 PSI (5.5 bar)

Jabsco

www.jabsco.com



USA
Jabsco
Cape Ann Industrial Park
Gloucester, MA 01930
Tel: (978) 281-0440
Fax: (978) 283-2619

UK
Jabsco
Bingley Road, Hoddesdon
Hertfordshire EN11 0BU
Tel: +44 (0) 1992 450145
Fax: +44 (0) 1992 467132

CANADA
Fluid Products Canada
55 Royal Road
Guelph, Ontario N1H 1T1
Tel: (519) 821-1900
Fax: (519) 821-2569

GERMANY
Jabsco GmbH
Oststrasse 28
22844 Norderstedt
Tel: +49-40-53 53 73-0
Fax: +49-40-53 53 73-11

JAPAN
NHK Jabsco Company Ltd.
3-21-10, Shin-Yokohama
Kohoku-Ku, Yokohama, 222
Tel: 045-475-8906
Fax: 045-475-8908

ITALY
Jabsco Marine Italia
Via Tommaseo, 6
20059 Vimercate, Milano
Tel: +39 039 685 2323
Fax: +39 039 666 307

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.