



# High Pressure Washdown Pump

## PAR-MAX SERIES

NEW! Jabsco® High Capacity Washdown Pumps

## NEW! High Capacity Washdown Pumps

- Flow rates to 7.5 GPM (29 LPM)
- Pressures up to 80 PSI (5.5 bar)
- Pumpgard™ Intake Strainer and Pressure Nozzle included (suitable for use in salt water)
- Corrosion resistant
- Soft rubber mounts
- Snap-fit port fittings
- 12 and 24 VDC models
- Self priming up to 6 feet (1.8m)
- ISO 8846 MARINE (ignition protection)
- CE



Pressure Nozzle & Pumpgard™ Intake Strainer included

Jabsco now offers boaters the highest capacity Washdown pump on the market today! Jabsco's complete range of Washdown pumps includes models with flows ranging from 3.5 to 7.5 GPM (13-29 LPM). The PAR-Max 6 washdown and the PAR-Max 8 washdown models are new to Jabsco, with pressures up to 80 PSI (5.5 bar). The high capacity performance characteristics match the needs of the larger vessel to wash decks and anchors clean. We include our quick connect 3/4" (19 mm) straight and 90° angled 3/4" (19 mm) hose barbs and QEST 1/2" – 14 straight and 90° angled pipe thread fittings for the 6.0 and 7.5 GPM models for ease of pump installation. All units come with a Pumpgard™ intake strainer, pressure nozzle and 3/4" (19 mm) adapter for nozzle attachment.

Specifications						
	Model (12V)	Amp Draw (A)	Model (24V)	Amp Draw (A)	PSI (bar)	GPM (LPM)
<b>PAR-Max 6</b>	41700-0092	9.0	41700-0094	4.5	80 (5.5)	6.0 (23)
<b>PAR-Max 8</b>	51700-0092	13.5	51700-0094	6.8	80 (5.5)	7.5 (29)

Jabsco





## PAR-Max High Capacity, High Pressure Washdown Pumps

**PAR-Max 6**  
**41700 Series**.....6.0 GPM (23 LPM)  
**Washdown Pump**

**PAR-Max 8**  
**51700 Series**.....7.5 GPM (29 LPM)  
**Washdown Pump**

### Product Features

- Flow rates to 7.5 GPM (29 LPM)
- Pressures up to 80 PSI (5.5 bar)
- Intake Strainer and Pressure Nozzle included
- Corrosion resistant
- Soft rubber mounts
- Snap-fit port fittings
- 12 and 24 VDC models
- Self priming up to 6 feet (1.8m)
- ISO 8846 MARINE (ignition protection)
- CE

### Specifications

**Materials** Pump Body.....Nylon  
Diaphragm.....Santoprene  
Valves.....EPDM  
Switch.....80 PSI (5.5 bar) cut off

**Temperature**  
Water.....Up to 160°F (70°C)

**Dimensions** PAR-Max 6.....6" H x 6.3" W x 12" L  
(152mm x 160mm x 305mm)

PAR-Max 8.....6" H x 6.3" W x 10" L  
(152mm x 160mm x 254mm)

**Weight** PAR-Max 6.....8lb. (3.6 kg)  
PAR-Max 8.....9.5lb. (4.3 kg)

**Open Flow** PAR-Max 6.....6 GPM (23 LPM)  
PAR-Max 8.....7.5 GPM (29 LPM)

**Typical Operating Pressure**  
PAR-Max 6/8.....60 PSI (4.1 bar)

**Shut-off Pressure**  
PAR-Max 6/8.....80 PSI (5.5 bar)

Jabsco

[www.jabsco.com](http://www.jabsco.com)



**ITT Industries**  
*Engineered for life*

**USA**  
Jabsco  
Cape Ann Industrial Park  
Gloucester, MA 01930  
Tel: (978) 281-0440  
Fax: (978) 283-2619

**UK**  
Jabsco  
Bingley Road, Hoddesdon  
Hertfordshire EN11 0BU  
Tel: +44 (0) 1992 450145  
Fax: +44 (0) 1992 467132

**CANADA**  
Fluid Products Canada  
55 Royal Road  
Guelph, Ontario N1H 1T1  
Tel: (519) 821-1900  
Fax: (519) 821-2569

**GERMANY**  
Jabsco GmbH  
Oststrasse 28  
22844 Norderstedt  
Tel: +49-40-53 53 73-0  
Fax: +49-40-53 53 73-11

**JAPAN**  
NHK Jabsco Company Ltd.  
3-21-10, Shin-Yokohama  
Kohoku-Ku, Yokohama, 222  
Tel: 045-475-8906  
Fax: 045-475-8908

**ITALY**  
Jabsco Marine Italia  
Via Tommaseo, 6  
20059 Vimercate, Milano  
Tel: +39 039 685 2323  
Fax: +39 039 666 307

Warranty: All products of the company are sold and all services of the company are offered subject to the company's warranty and terms and conditions of sale, copies of which will be furnished upon request. The information provided herein is for guidance only, it does not constitute a guarantee of the performance or specification of any individual product or component.