

JABSCO®

ELECTRIC WATER SYSTEM PUMPS

Models: 36800-0200 12 V
36800-0210 24 V
36900-0200 12 V
36900-0210 24 V
36950-2200 12 V
36950-2210 24 V

**DATA INSERT-
 LOW PRESSURE MODELS**

APPLICATION

The low pressure models are intended for use where the standard model exceeds the pressure requirements of a particular system. This may be when an instantaneous water heater is used in the system or other system components which may not tolerate higher pressures.

A drop in flow, under restricted flow conditions with some increase in pump cycling, may be noted.

An accumulator tank such as the Jabsco 12573-2000, 30573-0000, or 18810-0000 can be beneficial in a restrictive plumbing system.

SPECIFICATION

Cut-in Pressure: 10 psi Nominal (69kPa)
 Cut-out Pressure: 20 psi Nominal (138kPa)

NOTE: Cut-out pressure will vary slightly (+4 psi) between models and, to a lesser degree, between plumbing systems.

Other specifications remain essentially the same as the standard higher pressure model.

REPLACEMENT SWITCH

The only difference between the standard model and the low pressure model is the pressure switch (Key 13).

**FOR LOW PRESSURE MODELS
 ORDER SWITCH NUMBER:
 44814-1000**

Jabsco



ITT Industries
Engineered for life



THE PRODUCTS DESCRIBED HEREIN ARE SUBJECT TO THE JABSCO ONE YEAR LIMITED WARRANTY, WHICH IS AVAILABLE FOR YOUR INSPECTION UPON REQUEST.

U.S.A.
 Jabsco
 1485 Dale Way, P.O. Box 2158
 Costa Mesa, CA 92628-2158
 Tel: (714) 545-8251

Fax: (714) 957-0609
 UNITED KINGDOM
 Jabsco
 Bingley Road, Hoddesdon
 Hertfordshire EN11 0BU
 Tel: +44 (0) 1992 450145

Fax: +44 (0) 1992 467132
 CANADA
 Fluid Products Canada
 55 Royal Road
 Guelph, Ontario N1H 1T1
 Tel: (519) 821 -1900

Fax: (519) 821-2569
 JAPAN
 NHK Jabsco Company Ltd.
 3-21-10, Shin-Yokohama
 Kohoku-Ku, Yokohama, 222
 Tel: 045-4758906

Fax: 045-475-8908
 GERMANY
 Jabsco GmbH
 Oststrasse 28
 22844 Norderstedt
 Tel: +49-40-53 53 73 -0