

JABSCO®

ELECTRIC WATER SYSTEM PUMPS

Models: 36800-0200 12 V
36800-0210 24 V
36900-0200 12 V
36900-0210 24 V
36950-2200 12 V
36950-2210 24 V

DATA INSERT- LOW PRESSURE MODELS

APPLICATION

The low pressure models are intended for use where the standard model exceeds the pressure requirements of a particular system. This may be when an instantaneous water heater is used in the system or other system components which may not tolerate higher pressures.

A drop in flow, under restricted flow conditions with some increase in pump cycling, may be noted.

An accumulator tank such as the Jabsco 12573-2000, 30573-0000, or 18810-0000 can be beneficial in a restrictive plumbing system.

SPECIFICATION

Cut-in Pressure: 10 psi Nominal (69kPa)
Cut-out Pressure: 20 psi Nominal (138kPa)

NOTE: Cut-out pressure will vary slightly (+4 psi) between models and, to a lesser degree, between plumbing systems.

Other specifications remain essentially the same as the standard higher pressure model.

REPLACEMENT SWITCH

The only difference between the standard model and the low pressure model is the pressure switch (Key 13).

**FOR LOW PRESSURE MODELS
ORDER SWITCH NUMBER:
44814-1000**

Jabsco



ITT Industries
Engineered for life



THE PRODUCTS DESCRIBED HEREIN ARE SUBJECT TO THE JABSCO ONE YEAR LIMITED WARRANTY, WHICH IS AVAILABLE FOR YOUR INSPECTION UPON REQUEST.

U.S.A.
Jabsco
1485 Dale Way, P.O. Box 2158
Costa Mesa, CA 92628-2158
Tel: (714) 545-8251

Fax: (714) 957-0609
UNITED KINGDOM
Jabsco
Bingley Road, Hoddesdon
Hertfordshire EN11 0BU
Tel: +44 (0) 1992 450145

Fax: +44 (0) 1992 467132
CANADA
Fluid Products Canada
55 Royal Road
Guelph, Ontario N1H 1T1
Tel: (519) 821 -1900

Fax: (519) 821-2569
JAPAN
NHK Jabsco Company Ltd.
3-21-10, Shin-Yokohama
Kohoku-Ku, Yokohama, 222
Tel: 045-4758906

Fax: 045-475-8908
GERMANY
Jabsco GmbH
Oststrasse 28
22844 Norderstedt
Tel: +49-40-53 53 73 -0