



| Pos. | Qty. | Description    | Material | Dimension | Drawing no. |
|------|------|----------------|----------|-----------|-------------|
| 28   | 1    | Label          |          |           |             |
| 29   | 5    | Skriv          |          |           |             |
| 30   | 1    | Skriv          |          |           |             |
| 31   | 1    | Plugg          |          |           |             |
| 32   | 4    | Skriv          |          |           |             |
| 33   | 3    | Washer         |          |           |             |
| 34   | 3    | Skriv          |          |           |             |
| 35   | 1    | Washer         |          |           |             |
| 36   | 5    | Washer         |          |           |             |
| 37   | 1    | Clutch         |          |           |             |
| 38   | 2    | Retaining ring |          |           |             |
| 39   | 1    | Retaining ring |          |           |             |
| 40   | 2    | Ball bearing   |          |           |             |
| 41   | 1    | Mech. seal     |          |           |             |
| 42   | 1    | V-ring         |          |           |             |
| 43   | 1    | Retaining ring |          |           |             |
| 44   | 1    | Spacer         |          |           |             |
| 45   | 1    | Pedestal       |          |           |             |
| 46   | 1    | Wear plate     |          |           |             |
| 47   | 1    | Pin            |          |           |             |
| 48   | 1    | Gasket         |          |           |             |
| 49   | 1    | Impeller       |          |           |             |
| 50   | 1    | Cam            |          |           |             |
| 51   | 1    | Shaft          |          |           |             |
| 52   | 1    | End cover      |          |           |             |
| 53   | 1    | Body           |          |           |             |

Material: BPS-9  
Type: A-1  
Drawing no.: 10-13027

Det. No. 24 (34) to be locked with a tightening moment of 2.1 Nm  
Det. No. 24 (34) to be locked with a tightening moment of 2.1 Nm  
NOTE Label 01-35171 is to be placed in centre of endcover 01-4806

|             |             |             |              |
|-------------|-------------|-------------|--------------|
| 10-13027    | 10-13027    | 10-13027    | 10-13027     |
| 10-13027-01 | 10-13027-02 | 10-13027-03 | 10-13027-04  |
| 10-13027-05 | 10-13027-06 | 10-13027-07 | 10-13027-08  |
| 10-13027-09 | 10-13027-10 | 10-13027-11 | 10-13027-12  |
| 10-13027-13 | 10-13027-14 | 10-13027-15 | 10-13027-16  |
| 10-13027-17 | 10-13027-18 | 10-13027-19 | 10-13027-20  |
| 10-13027-21 | 10-13027-22 | 10-13027-23 | 10-13027-24  |
| 10-13027-25 | 10-13027-26 | 10-13027-27 | 10-13027-28  |
| 10-13027-29 | 10-13027-30 | 10-13027-31 | 10-13027-32  |
| 10-13027-33 | 10-13027-34 | 10-13027-35 | 10-13027-36  |
| 10-13027-37 | 10-13027-38 | 10-13027-39 | 10-13027-40  |
| 10-13027-41 | 10-13027-42 | 10-13027-43 | 10-13027-44  |
| 10-13027-45 | 10-13027-46 | 10-13027-47 | 10-13027-48  |
| 10-13027-49 | 10-13027-50 | 10-13027-51 | 10-13027-52  |
| 10-13027-53 | 10-13027-54 | 10-13027-55 | 10-13027-56  |
| 10-13027-57 | 10-13027-58 | 10-13027-59 | 10-13027-60  |
| 10-13027-61 | 10-13027-62 | 10-13027-63 | 10-13027-64  |
| 10-13027-65 | 10-13027-66 | 10-13027-67 | 10-13027-68  |
| 10-13027-69 | 10-13027-70 | 10-13027-71 | 10-13027-72  |
| 10-13027-73 | 10-13027-74 | 10-13027-75 | 10-13027-76  |
| 10-13027-77 | 10-13027-78 | 10-13027-79 | 10-13027-80  |
| 10-13027-81 | 10-13027-82 | 10-13027-83 | 10-13027-84  |
| 10-13027-85 | 10-13027-86 | 10-13027-87 | 10-13027-88  |
| 10-13027-89 | 10-13027-90 | 10-13027-91 | 10-13027-92  |
| 10-13027-93 | 10-13027-94 | 10-13027-95 | 10-13027-96  |
| 10-13027-97 | 10-13027-98 | 10-13027-99 | 10-13027-100 |