




COMPLETE RANGE OF RUBBER IMPELLER PUMPS



Self-priming electric pump with flexible rubber impeller. Now available in 3 different flow rates: 7.4, 9.25 and 11.9 gpm.

Fitted with water proof cable guide and internal brush holder with EMI filter. ISO 8846 and ISO 8849.

Ideal for bilge and waste water on any type of boat.

UP1-J NEW

UP1-N BEST SELLER

UP1-M NEW



PART NUMBER	UP1- J		UP1- N		UP1- M	
	M162-004-12	M162-004-13	M162-002-12	M162-002-13	M162-006-12	M162-006-13
VOLTS	12	24	12	24	12	24
SELF-PRIMING	5 ft	5 ft	5 ft	5 ft	5 ft	5 ft
PRESSURE	14.5 psi	14.5 psi	14.5 psi	14.5 psi	21.8 psi	21.8 psi
FLOW RATE	7.4 gpm	7.4 gpm	9.25 gpm	9.25 gpm	11.9 gpm	11.9 gpm
CONSUMPTION	8A	4A	10A	5A	14A	7A
FUSE	10A	7.5A	20A	15A	20A	15A
PORTS	3/8" BSP int. Ø 3/4" ext.	3/8" BSP int. Ø 1" ext.	1/2" BSP int. Ø 1" ext.	1/2" BSP int. Ø 1" ext.	1/2" BSP int. Ø 1" ext.	1/2" BSP int. Ø 1" ext.