

**LOW  
SPEED**

## COMPLETE RANGE OF OIL TRANSFER PUMPS

UP2/OIL



UP3/OIL  
UP4/OIL



UP6/OIL



UP12/OIL



Self-priming electric pumps with helical bronze gears for transferring lubricating oils and viscous liquids. Nickel-plated brass body and stainless steel shaft. Particularly suitable for draining engine sumps with the special tubes kit (OK1) and for engines lubricating operations.

| TYPE     | PART NUMBER | VOLTS | SELF-PRIM. | FLOW RATE* |           |            | CONSUMPTION | FUSE | PORTS male |
|----------|-------------|-------|------------|------------|-----------|------------|-------------|------|------------|
|          |             |       |            | ø 1/4"     | ø 5/16"   | ø 15/32"   |             |      |            |
| UP2/OIL  | M164-220-12 | 12    | 3,3 ft     | 4,8 gph    | 14,3 gph  | 52,9 gph   | 2,3A ÷ 2,7A | 3A   | 3/8" NPT   |
|          | M164-220-13 | 24    | 3,3 ft     | 4,8 gph    | 14,3 gph  | 52,9 gph   | 1,1A ÷ 1,4A | 1,5A | 3/8" NPT   |
|          |             |       |            | ø 1/4"     | ø 5/16"   | ø 9/16"    |             |      |            |
| UP3/OIL  | M164-020-12 | 12    | 3,3 ft     | 5,30 gph   | 15,90 gph | 87,20 gph  | 5,5A ÷ 6,5A | 7,5A | 3/8" NPT   |
| UP4/OIL  | M164-020-13 | 24    | 3,3 ft     | 5,30 gph   | 15,90 gph | 87,20 gph  | 2,5A ÷ 3,5A | 4A   | 3/8" NPT   |
|          |             |       |            | ø 1/4"     | ø 5/16"   | ø 9/16"    |             |      |            |
| UP6/OIL  | M164-080-12 | 12    | 4,9 ft     | 6,60 gph   | 19,82 gph | 126,82 gph | 6,5A ÷ 8,5A | 10A  | 1/2" NPT   |
|          | M164-080-13 | 24    | 4,9 ft     | 6,60 gph   | 19,82 gph | 126,82 gph | 3,5A ÷ 4,5A | 7,5A | 1/2" NPT   |
|          |             |       |            | ø 15/32"   | ø 5/8"    |            |             |      |            |
| UP12/OIL | M164-320-12 | 12    | 6,6 ft     | 95 gph     | 238 gph   |            | 11A ÷ 12A   | 15A  | 1/2" NPT   |
|          | M164-320-13 | 24    | 6,6 ft     | 95 gph     | 238 gph   |            | 5,5A ÷ 6,5A | 7,5A | 1/2" NPT   |

\* OIL SAE 30 AT 77°F