

1" TO 3", UP TO 500 GPM, UP TO 300 TDH, WITH MULTIPLE SEAL OPTIONS

Price Pump manufactures a versatile line of centrifugals that have multiple seal options including flush, quench, double seals, and hardened faces. Their standard C-face and "JM" mounting allow a multitude of drive enclosures, voltages, and custom orientations (hydraulic, pneumatic, clutch, etc.).

UP TO 160 GPM, 100 TDH


- Temperatures to 300° F
- Semi-open impeller
- Housing Construction: 316SS, Cast Iron or Bronze
- Multiple Seal Options: Buna, Neoprene, Viton, EPR and Teflon, Single and Double Mechanical, Silicon and Tungsten Carbide Faces, Seal Flush or Quench
- Drive Options: pedestal mount, Hydraulic, Pneumatic, AC and DC voltages, single and three phase, ODP, TEFC, explosion proof, and custom configurations

UP TO 400 GPM, 75 TDH

- Temperatures to 300° F
- Semi-open impeller
- Housing Construction: all Iron and Bronze fitted Cast Iron
- Multiple Seal Options: Buna, Neoprene, Viton, EPR and Teflon, single and double mechanical, Silicon and Tungsten Carbide faces, seal flush or quench
- Drive Options: pedestal mount, Hydraulic, Pneumatic, AC and DC voltages, single and three phase, ODP, TEFC, explosion proof and custom configurations


UP TO 500 GPM, 300 TDH


- Temperatures to 300° F
- Enclosed impeller
- 150 lb. Centerline ANSI flanges or NPT threaded ports
- Housing Construction: 316SS in flanged or threaded ports, Cast Iron or Bronze in threaded ports
- Multiple seal options
- Drive Options: pedestal mount, single and three phase, ODP, TEFC, explosion proof, and custom configurations











FOR ENGINEERING AND PUMP SELECTION ASSISTANCE CALL DEPCO AT 1-800-446-1656