General Purpose Pumps



PUMP

Type: 3 Chamber Diaphragm 3/8" NPT-Female Ports: Liquid: 130 °F [54 °C] Max Prime: 6 feet [1.82 M] 30 PSI [2.1 Bar] Max Inlet PSI: Run Dry: Yes

ELECTRICAL

Motor:	12VDC Permanent Magnet, Continuous Duty		
Protection:	Thermal Overload		
Leads:	16 AWG, 16" [40 cm] Red +, 13" [33 cm] Black -		
Fuse:	7.5 Amp Recommended		
Control:	35 PSI Internal By-Pass		

MATERIALS

Polypropylene Housing: Valves: Buna Diaphragm: Geolast 87 Shore Hardware: Stainless Steel

APPROVALS

c-UL Marine, Ignition Protected, ISO 8846

WARRANTY

1 Year Limited Warranty See SB-1041 & SB-1050 For Full Warranty Details


SHIPPING

Net Weight (Boxed):	28 Lb [12.7 Kg] each
Carton Weight:	6 each, Lb [Kg]
Carton Size:	24"L x 18"W x 6"H
	[61 cm x 46 cm x 15 cm]

RELATED DOCUMENTS

MS-030-140
911-714
911-314
MS-020-005
SB-1050

Parts Kits Number Components Parts Kits





PDS 8050-305-526

MARINE PRODUCT DATA SHEET OEM: N/A AFTERMARKET: 8050-305-526


Incorporating SHURflo's advance motor technology that includes thermal overload protection, these pumps are self-priming, easy to install and are extremely versatile-perfect for a variety of uses including winterizing, Oil changing and liquid transfer.

TYPICAL APPLICATIONS


Oil change, winterizing, automatic transmission fluids, anti-freeze solutions, low viscosity gear and liquid transfer. Other uses may include 12 VDC pressurized water systems, For other applications contact SHURflo.

PRESSURE		FLOW		CURRENT
BAR	PSI	GPM	LPM	AMPS
0.0	0	1.55	5.86	2.2
0.7	10	1.45	5.48	2.8
1.4	20	1.36	5.14	3.5
2.1	30	1.10	4.16	4.1
2.8	40	0.15	0.56	4.4

PERFORMANCE @ 12V DC WITH WATER



TYPICAL MOTOR SHELL T-RISE @ 40 PSI, 12V





*ISO Registered Facility SHURflo reserves the right to update specifications, prices, or make substitutions.

SHURflo * 5900A Katella Ave. Cypress, Ca. 90630 (800) 854-3218 (562) 795-5200 FAX (562) 795-7554 Shipping/UPS: 5900C Katella Ave. Cypress, Ca. 90630 SHURflo East 52748 Park Six Court Elkhart, IN 46514-5427 (800) 762-809 (574) 262-0478 FAX (574) 264-2169 Http://www.shurflo.com ©2001



United Kingdom

+44 1293 424000

FAX +44 1293 421880