


DOSING CONTROL

ETIMED APPLICATIONS

The Econ T is a compact, easy to program pump with flexibility to schedule up to 24 separate events within a 7 day period



The automatic dosing control is reliable for timed applications including injection of enzymes for drain line maintenance and biocide feed in small cooling towers or water fountains.

Control panel features a 24 hour integral clock that has a battery backup to maintain the time of day.



0.6 to 1.3 gpd @ 80 psi 2.5 to 15 gpd @ 25 psi

Wall Mountable

Simple Programming with LCD Display

Effortless Tube Replacement








Econ T is ideal for light duty applications

- · Patented quick release pump head design
- · Solid one piece tube construction
- · UL & cUL listed
- · NSF 61 & 372 listed for USA & Canada
- · 4 lbs
- · 5.3" | x 3.6" w x 5.8" h

Optional Mounting Accessories



Mounting Kit EC303For Stenner Tank or wall mount



Stand EC304
For horizontal display
or wall mount

Outputs

| Item Number Prefix | Pump Tube | Roller Assembly | Gallons per Day | Gallons per Hour | Ounces per Minute | Pressure psi | Liters per Day | Liters per Hour | Milliliters per Minute | |
|-----------------------|--------------|--------------------|--------------------|---------------------|----------------------|--------------|-------------------|--------------------|---------------------------|-----|
| E10T1F | F | White | 0.6 | 0.02 | 0.05 | 80 | 2.2 | 0.09 | 1.5 | 5.5 |
| E10T2F | F | White | 1.3 | 0.05 | 0.11 | 80 | 4.8 | 0.20 | 3.3 | 5.5 |
| E10T1A | Α | White | 2.5 | 0.10 | 0.22 | 25 | 9.5 | 0.39 | 6.6 | 1.7 |
| E10T2A | Α | White | 5.0 | 0.21 | 0.44 | 25 | 18.9 | 0.79 | 13.1 | 1.7 |
| E10T2B | В | White | 8.5 | 0.35 | 0.76 | 25 | 32.2 | 1.34 | 22.3 | 1.7 |
| E10T2C | С | White | 15.0 | 0.63 | 1.33 | 25 | 56.8 | 2.37 | 39.4 | 1.7 |
| | | | | | Annroxima | te Maximu | m Outputs | @ 50/60H | 7 | |

Approximate Maximum Outputs @ 50/ 60Hz

Build An Item Number

Select **Item Number Prefix** from output chart above

Leave blank if not ordering a tank system

Tank

 $\textbf{S7N}\ 7.5$ Gallon White

S1N 15 Gallon White

S3N 30 Gallon White

NOTE: Tanks also sold separately.

Voltage & Hertz/Cord

7 120V 60Hz; 6' cord

8 120V 60Hz; 10' cord

Suction & Discharge Tubing

1 1/4" White

Tube Material

1

S Santoprene®

This information is not intended for specific application purposes. Stenner Pump Company reserves the right to make changes to prices, products, and specifications at any time without prior notice.





