

PROPORTIONAL INJECTION SYSTEM

ACCURATE AND REPEATABLE DOSAGES

STENNER PUMPS

*PRE-ASSEMBLED PANEL
CONVENIENTLY MOUNTS TO THE WALL*

Panel and wall mount brackets included

- ✓ pH Adjustment
- ✓ Iron Stain Removal
- ✓ Bacteria Reduction
- ✓ Oxidation

*Cabinet keeps cords
and wires contained*

*Unions for easy installation
and removal*

*Chemical resistant
polyethylene panel*

*30 & 100 mesh
flushable filters
included*



DUAL ALSO AVAILABLE



ACCURATE AND REPEATABLE DOSES

The Proportional Injection System delivers precise dosing proportional to the system's flow rate based on water volume. The system is pre-assembled on a panel that conveniently mounts to the wall for timely installations and equipment accessibility.



Stenner Pump Company
Jacksonville, Florida USA
www.stenner.com

800.683.2378
904.641.1666

Stenner products are
proudly made in the USA

© Stenner Pump Company
All Rights Reserved

PROPORTIONAL INJECTION SYSTEM

Build Item Number

		1				
System Type	Pump	Voltage & Hertz	Pump Control Module	Water Meter		

Item number is required for placing orders. To build item number, select code based on application requirements.

System Type	S Single
	D Dual

Pump			Fixed
	gpd	lpd	
03	3	11.4	45MPHP2
05	5	18.9	85MPHP5
10	10	37.9	45MPHP10
17	17	64.4	85MPHP17
22	22	83.3	45MPHP22
40	40	151.4	85MPHP40

Pump and Pump Control Module Voltage	1 120V 60Hz
---	--------------------

Pump Control Module			Model
	Seconds		
01	0.1 to 1.0		PCM1
05	0.5 to 5.0		PCM 5
10	1.0 to 10.0		PCM 10
20	2.0 to 20.0		PCM 20

Water Meter	751G 3/4" 1 gallon/pulse
	752P 3/4" 2 pulse/gallon
	754P 3/4" 4 pulse/gallon

NOTE: Additional pulse rates available with two week lead time, contact factory.

Specifications

Materials

Panel & panel fittings: Polyethylene

Mounting hardware: Stainless steel

Piping and associated fittings: PVC

Water meter: Bronze

Filter: PVC with polycarbonate cover and two polyester screens 30 and 100 mesh

NOTE: PVC connections are socket weld union 3/4" connections. Two 1" to 3/4" reducer couplings are included in the accessory kit to allow unit to adapt to 1" piping systems.

Dimensions: w x h

Single: 28" x 17.5" (71.1 x 44.5 cm)

Dual: 36.2" x 22.1" (91.9 x 56.2 cm)

Shipping Weight

Single: 31 lbs (14 kg)

Dual: 45 lbs (20.4 kg)

