

Frame Mounted End Suction, Flanged Connection

Pump Model	Size	Suction/Discharge 125# Flange Rating	Suction/Discharge 300# Flange Rating
		Maximum Casing Working Pressure (PSI) -20 to 150F	Maximum Casing Working Pressure (PSI) -20 to 150F
1G	1 x 1.25 x 7	175	450
1.5G1	1.5 x 2 x 7B	175	450
1.5G	1.5 x 2 x 7	175	450
1.5GT	1.5 x 3 x 7	175	450
1.5K	1.5 x 2 x 9	175	450
1.5K1	1.5 x 2 x 9B	175	450
1.5KH	1.5 x 2 x 12	175	450
2G	2 x 3 x 7	175	450
2K	2 x 3 x 9	175	450
2.5G	2.5 x 3 x 7	175	450
2.5K	2.5 x 3 x 9	175	450
2.5KH1	2.5 x 3 x 12B	175	450
2.5KH	2.5 x 3 x 12	175	450
3G	3 x 4 x 7	175	450
3K	3 x 4 x 9B	175	450
3K1	3 x 4 x 9	175	450
3KH	3 x 4 x 12B	175	450
3KH1	3 x 4 x 12	175	450
4G	4 x 5 x 7	175	450
4G1	4 x 5 x 7B	175	450
4GL	4 x 5 x 7L	175	450
4K	4 x 5 x 12	175	450
4KL	4 x 5 x 9	175	450
4KS	4 x 5 x 13	175	450
5G	5 x 6 x 9	175	N/A
6G	6 x 8 x 9	175	N/A
6K	6 x 8 x 12	175	450