

## Tiptoe Pump Mk 4

### Self-Priming Foot Pump

- Smooth and easy operating action
- Easy to install thru deck design
- Comfortable for bare-foot use
- Plunger safely locks down ensuring the pump is flush with floor level when not in use
- Suitable for pumping freshwater and saltwater
- Capacity is 7 ltrs (1.85 US gals) per minute
- Ideal as a priming pump for use with the Whale In-Line Electric Pumps (see page 9)

#### Model Specifications

<b>Model</b>	<b>Tiptoe</b>
<b>Product Code</b>	<b>GP1309</b>
Hose Connections	Suitable for 13 mm (1/2") Flexible Hose
Weight	0.4 kg (0.9 lbs)
Materials	Pump Body: Acetal, Nylon, Polypropylene Seals: Neoprene, Nitrile, Phosphor Bronze, Fasteners: Stainless Steel
Service Kit	AK1304 - Service Kit for Tiptoe Mk 3 and Mk 4 Models Contains: Washers, Valve Plates, Circlips
Maximum Suction Lift	2 m (7 ft)
Maximum Discharge Head	4 m (12 ft)
Maximum Output per Minute	7 ltrs (1.85 US gals)


## Babyfoot® Pump

### Self-Priming Compact Foot Pump


- Smooth and easy operating action
- Easy to install compact design
- Ideal for installation where space is limited
- Angled design ensures more comfortable operation
- Ideal as a priming pump for use with Whale In-Line Electric Booster Pumps (see page 9)
- Suitable for pumping freshwater and saltwater

#### Model Specifications


<b>Model</b>	<b>Babyfoot®</b>
<b>Product Code</b>	<b>GP4618</b>
Hose Connections	Suitable for 13 mm (1/2") Flexible Hose
Weight	0.3 kg (0.7 lbs)
Materials	Pump Body: Nylon, Ports: Acetal, Seals: Neoprene Fasteners: Stainless Steel, Phosphor Bronze
Service Kit	AK4615 - Service Kit for Babyfoot® Pump Contains: Diaphragm Valves, O Rings, Spring, Fasteners
Maximum Suction Lift	1.5 m (5 ft)
Maximum Discharge Head	3 m (10 ft)
Maximum Output per Minute	8 ltrs (2.2 US gals)



Front View




Side View



Plan View



**GP1309**  
**Tiptoe Pump Mk 4**  
5 Year Warranty



Side View



**GP4618**  
**Babyfoot® Pump**  
5 Year Warranty