

JABSCO AND FLOJET WATER SYSTEMS

CONTENTS

ENGINE COOLING

INDEX

HOME

NEXT

BACK

FLOJET




Quad Series

3.3 - 4.5 GPM FLOJET WATER SYSTEM PUMPS

The Flojet "Quiet Quad" delivers smooth generous flow and does not require an accumulator tank! Additional models are available for existing systems with accumulator tanks. See page 149 for service parts.

Model	Max. GPM	Volts	Amps at 10 PSI	Inlet/Outlet	Pressure Switch	Requires Accumulator	Dimensions (H x W x L)
FJ 04405-143	3.3	12 vdc	3.9	1/2" Barb & 1/2" Qest	35 psi	No	3.9" x 6.3" x 8.3"
FJ 04405-343	3.3	24 vdc	2.0	1/2" Barb & 1/2" Qest	35 psi	No	3.9" x 6.3" x 8.3"
FJ 04405-443	3.3	32 vdc	1.3	1/2" Barb & 1/2" Qest	35 psi	No	3.9" x 6.3" x 8.3"
FJ 04406-043	3.3	115 vac	0.4	1/2" Barb & 1/2" Qest	35 psi	No	3.9" x 6.3" x 8.3"
FJ 04405-500	3.3	12 vdc	3.9	1/2" Barb & 1/2" Qest	35 psi	Yes	3.9" x 6.3" x 8.3"
FJ 04405-501	3.3	24 vdc	2.0	1/2" Barb & 1/2" Qest	35 psi	Yes	3.9" x 6.3" x 8.3"
FJ 04325-143	4.5	12 vdc	6.0	3/4" Barb & 3/4" GHT	40 psi	No	3.9" x 6.3" x 9.9"
FJ 04325-343	4.5	24 vdc	2.5	3/4" Barb & 3/4" GHT	40 psi	No	3.9" x 6.3" x 9.9"
FJ 04325-443	4.5	32 vdc	2.0	3/4" Barb & 3/4" GHT	40 psi	No	3.9" x 6.3" x 9.9"

FLOJET



12, 24 & 32 vdc and 115 vac

4.5 GPM "BASE MOUNTED" PUMP WITH ACCUMULATOR

Flojet's compact 2840 series water system utilizes the dependable "Quiet Quad" displayed above. Each system has an accumulator tank, will function at any angle, and will self-prime to 10 feet! See page 149, series 4325 for service parts.

Model	Max. GPM	Volts	Max. Amps	Inlet	Outlet	Dimensions (H x W x L)
FJ 02840-100	4.5	12 vdc	10.0	3/4" Barb	1/2" Barb/Qest	7.50" x 11.25" x 12.875"
FJ 02840-300	4.5	24 vdc	5.0	3/4" Barb	1/2" Barb/Qest	7.50" x 11.25" x 12.875"
FJ 02840-400	4.5	32 vdc	3.8	3/4" Barb	1/2" Barb/Qest	7.50" x 11.25" x 12.875"
FJ 02840-000	4.5	115 vac	1.5	3/4" Barb	1/2" Barb/Qest	7.50" x 11.25" x 12.875"

JABSCO / FLOJET




PAR-MAX

2.3 GPM JABSCO/FLOJET WATER SYSTEM PUMPS

These two chamber diaphragm pumps provide dependable flow to multiple outlets at an affordable price. They deliver up to 2.3 gpm, incorporate a 20 psi demand pressure switch, 3/8" FPT ports with 1/2" hose barb adapters.

Model	Max. GPM	Volts	Amps at 10 PSI	Inlet/Outlet	Dimensions (H x W x L)
FJ 02100-12	2.3	12 vdc	5.0	3/8" FPT and 1/2" Barb	3.6" x 4" x 8"
JA 46010-2900	2.3	12 vdc	5.0	3/8" FPT and 1/2" Barb	3.75" x 3.25" x 8.2"
JA 46010-2901	2.3	24 vdc	2.5	3/8" FPT and 1/2" Barb	3.75" x 3.25" x 8.2"

JABSCO



Ultra Max

3.8 GPM "BASE MOUNTED" PUMP WITH ACCUMULATOR

The Jabasco Ultra-Max water system series is assembled with a one liter accumulator tank on an easy to mount corrosion proof base with noise isolating rubber mounts. They have a very low profile (see dimensions), will prime to 5 feet and can be mounted in any position. See page 153, series 31620 for service parts. See page 153, series 30620 for service parts on the superceded 59450 series.

Model	Max. GPM	Volts	Max. Amps	Inlet	Outlet	Dimensions (H x W x L)
JA 59451-1012	3.8	12 vdc	12	1/2" Barb/Qest	1/2" Barb/Qest	5.5" x 15.25" x 15.5"
JA 59451-1024	3.8	24 vdc	6	1/2" Barb/Qest	1/2" Barb/Qest	5.5" x 15.25" x 15.5"