

CONTENTS

1 TO 4 GPM, "AQUA KING" WATER SYSTEMS

The new "Aqua King" diaphragm pumps from Shurflo replace the popular 2088 series. Designed and built specifically for the harsh marine environment, these next generation pumps include sealed switches and seamless e-coated motors. See page 64 for other port fitting options and page 152 for service parts.

ENGINE COOLING

INDEX

HOME

NEXT

BACK

Model	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 1901-0013	1.0	12vdc	3 amps	30	1/2" Barb & 1/2" Qest MPT	3.2" x 4.5" x 6.4"
SF 2901-0213	2.0	12vdc	4 amps	30	1/2" Barb & 1/2" Qest MPT	5.0" x 4.6" x 7.3"
SF 3901-0216	3.0	12vdc	6 amps	55	1/2" Barb & 1/2" Qest MPT	5.0" x 4.6" x 7.3"
SF 3901-1216	3.0	24vdc	3 amps	55	1/2" Barb & 1/2" Qest MPT	5.0" x 4.6" x 7.3"
SF 4901-4212	4.0	12vdc	10 amps	45	1/2" Barb & 1/2" Qest MPT	5.4" x 5.3" x 7.2"

SHURFLO



Aqua King

1 TO 5 GPM, "SMART SENSOR" WATER SYSTEMS

The Extreme series "Smart Sensor" pumps from Shurflo utilize a micro-controller to control the speed of the motor to deliver a smooth variable flow to match the number of fixtures in use at any time. All models have a corrosion resistant coated seamless motor shell and protected electronics capable of handling the harsh marine environment. The 5901 series comes with 1/2" MPT quick connect ports. Also available: 1/2" barb (94-615-01 straight/94-615-00 elbow) and 3/4" barb (94-615-04 straight/94-615-05 elbow). See page 64 for port fitting options for the 4901 series and page 152 for service parts on all models.

Model	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 4901-0211	4.0	12 vdc	9 amps	50	1/2" Barb or 1/2" Qest MPT	5.4" x 5.3" x 7.2"
SF 4901-1211	4.0	24/32 vdc	5 amps	50	1/2" Barb or 1/2" Qest MPT	5.4" x 5.3" x 7.2"
SF 5901-0211	5.0	12 vdc	10 amps	60	1/2" Quest MPT	5.0" x 5.5" x 9.25"
SF 5901-1211	5.0	24/32 vdc	5 amps	60	1/2" Quest MPT	5.0" x 5.5" x 9.25"

SHURFLO




Smart Sensor

4 AND 5.5 GPM, "EXTREME" SERIES WATER SYSTEMS WITH ACCUMULATOR

The Extreme series pumps with accumulator from Shurflo are fully automatic and come complete with suction strainer and NSF certified stainless steel 2 gallon accumulator tank. The 4902 series supplies up to 4 gpm and comes equipped with a 45 psi pressure switch. The 5902 series supplies up to 5.5 gpm and also comes equipped with a 45 psi pressure switch. See page 152 for service parts on both sizes.

Model	Max GPM	Volts	Max Amps	Max PSI	Inlet/Outlet	Dimensions (H x W x L)
SF 4902-2212	4.0	12 vdc	10 amps	45	3/4" Barb or 1 1/2" Qest MPT	14.5" x 13" x 14"
SF 5902-2212	5.5	12 vdc	12.4 amps	45	3/4" Barb or 1 1/2" Qest MPT	14.5" x 13" x 14"
SF 5902-3212	6.5	24 vdc	6 amps	45	3/4" Barb or 1 1/2" Qest MPT	14.5" x 13" x 14"

SHURFLO



Accumulator System

3.4 - 5.0 GPM AQUA-JET WATER SYSTEM PUMPS

The Aqua-Jet five chambered diaphragm pump design demonstrates dramatically lower noise and water pulsation than traditional pump configurations. They come standard with a 40 psi switch and are available in 12 and 24 vdc in flows up to 5.0 GPM. An accumulator tank is recommended (see page 20).

Model	Max. GPM	Volts	Amps	Inlet / Outlet	Dimensions (H x W x L)
JS 10-13250-103	3.4	12 vdc	8.5	1/2" Barb	4.50" x 8.22" x 9.4"
JS 10-13250-104	3.4	24 vdc	3.4	1/2" Barb	4.50" x 8.22" x 9.4"
JS 10-13250-107	5.0	12 vdc	11.5	1/2" Barb	4.50" x 8.22" x 9.4"
JS 10-13250-108	5.0	24 vdc	5.1	1/2" Barb	4.50" x 8.22" x 9.4"

JOHNSON



Aqua-Jet