

WASHDOWN PUMPS

CONTENTS

ENGINE COOLING

INDEX

HOME

NEXT

BACK

JABSCO



Par Max 6 and 8

6 AND 7.5 GPM, 80 PSI JABSCO WASHDOWN PUMPS

The new "PAR-Max" 5 chambered diaphragm pumps by Jabsco deliver up to 7.5 gpm and 80 psi to meet the demands of deck and anchor washing for vessels 60 feet and larger. They will prime up to 6 feet and come complete with intake strainer, spray nozzle and 3/4" barbed fittings.

Model Number	Max GPM	Volts	Fuse Size	Inlet/Outlet	Dimensions (H x W x L)
JA 41700-0092	6.0	12 vdc	25 amps	3/4" Barb	6" x 6.3" x 12"
JA 41700-0094	6.0	24 vdc	25 amps	3/4" Barb	6" x 6.3" x 12"
JA 51700-0092	7.5	12 vdc	30 amps	3/4" Barb	6" x 6.3" x 12"
JA 51700-0094	7.5	24 vdc	30 amps	3/4" Barb	6" x 6.3" x 12"

SHURFLO



Extreme Pro Blaster

5.5 GPM, 45 PSI SHURFLO WASHDOWN PUMPS

The new extreme "ProBlaster" 5 chambered diaphragm pumps by Shurflo deliver up to 5.5 gpm and 45 psi. They are constructed with a corrosion resistant coated seamless motor shell and sealed switch to provide excellent protection against the harsh marine environment. They come standard with 1/2" MPT ports. The 5901 series comes with 1/2" MPT quick connect ports. Also available: 1/2" barb (94-615-01 straight/94-615-00 elbow) and 3/4" barb (94-615-04 straight/94-615-05 elbow). See page 152 for service parts.

Model Number	Max GPM	Volts	Max Amps	Inlet/Outlet	Dimensions (H x W x L)
SF 5901-2212	5.5	12 vdc	12	3/4" MPT	5" x 5.5" x 9.25"
SF 5901-3212	5.5	24 vdc	6	3/4" MPT	5" x 5.5" x 9.25"

SHURFLO



Blaster and Pro Blaster

3.5 AND 4.0 GPM, 45 PSI SHURFLO WASHDOWN PUMPS

The new "Blaster" and "ProBlaster" 3 and 4 chambered diaphragm pumps by Shurflo deliver up to 4.0 gpm and 45 psi. They are constructed with a corrosion resistant coated seamless motor shell and sealed switch to provide excellent protection against the harsh marine environment. They come standard with 1/2" MPT ports. See page 64 for other port fittings and page 152 for service parts.

Model Number	Max GPM	Volts	Max Amps	Inlet/Outlet	Dimensions (H x W x L)
SF 3901-2214	3.5	12 vdc	9	1/2" MPT and 3/4" Barb	5" x 4.6" x 7.3"
SF 3901-3214	3.5	24 vdc	4.5	1/2" MPT and 3/4" Barb	5.4" x 5.3" x 7.2"
SF 4901-4282	4.0	12 vdc	10	1/2" MPT and 3/4" Barb	5" x 4.6" x 7.3"
SF 4901-5282	4.0	24 vdc	5.5	1/2" MPT and 3/4" Barb	5.4" x 5.3" x 7.2"

JOHNSON



Aqua Jet 3.4 and 5.0

3.4 AND 5.0 GPM, 70 PSI JOHNSON WASHDOWN PUMPS

The new "Aqua Jet" 5 chambered diaphragm pumps by Johnson deliver up to 5.0 gpm and 70 psi. They will prime up to 6 feet and come complete with intake strainer, spray nozzle and 1/2" barbed fittings.

Model Number	Max GPM	Volts	Max Amps	Inlet/Outlet	Dimensions (H x W x L)
JS 10-13251-103	3.4	12 vdc	15 Amps	1/2" MPT and 3/4" Barb	4.49" x 8.22" x 9.4"
JS 10-13251-104	3.4	24 vdc	8 Amps	1/2" MPT and 3/4" Barb	4.49" x 8.22" x 9.4"
JS 10-13251-107	5.0	12 vdc	20 Amps	1/2" MPT and 3/4" Barb	4.49" x 8.22" x 9.4"
JS 10-13251-108	5.0	24 vdc	10 Amps	1/2" MPT and 3/4" Barb	4.49" x 8.22" x 9.4"