

CONTENTS

4 GPM, 60 PSI WASHDOWN PUMP KIT

The new "Par-Max" 4 gpm washdown model offers pressures up to 60 psi with 3 chamber smooth performance. Pumps have a sealed motor and pressure switch for mounting in exposed positions. Kit comes with intake strainer, spray nozzle and 3/4" quick connect hose barb fittings. 32900-Series include a 25ft hose coil.

Model Number	Max GPM	Volts	Amps at:		Inlet/Outlet	Dimensions (H x W x L)
			10 PSI	40PSI		
JA 32605-0092	4	12 vdc	5	9	3/4" Barb	4.0" x 4.0" x 7.8"
JA 32605-0094	4	24 vdc	3	6	3/4" Barb	4.0" x 4.0" x 7.8"
JA 32900-0092	4	12 vdc	5	9	3/4" Barb	4.0" x 4.0" x 7.8"
JA 32900-0094	4	24 vdc	4	6	3/4" Barb	4.0" x 4.0" x 7.8"



5.5 GPM, 45 PSI SHURFLO WASHDOWN PUMPS

The new extreme "ProBlaster" 5 chambered diaphragm pumps by Shurflo deliver up to 5.5 gpm and 45 psi. They are constructed with a corrosion resistant coated seamless motor shell and sealed switch to provide excellent protection against the harsh marine environment. They come standard with 1/2" MPT ports. The 5901 series comes with 1/2" MPT quick connect ports. Also available: 1/2" barb (94-615-01 straight/94-615-00 elbow) and 3/4" barb (94-615-04 straight/94-615-05 elbow). See page 158 for service parts.

Model Number	Max GPM	Volts	Max Amps	Inlet/Outlet	Dimensions (H x W x L)
SF 5901-2212	5.5	12 vdc	12	3/4" MPT	5" x 5.5" x 9.25"
SF 5901-3212	5.5	24 vdc	6	3/4" MPT	5" x 5.5" x 9.25"
SF 5901-4212	5.5	32 vdc	5	3/4" MPT	5" x 5.5" x 9.25"



2.0 - 4.0 GPM, 45 PSI SHURFLO WASHDOWN PUMPS

The new "Blaster" and "ProBlaster" 3 and 4 chambered diaphragm pumps by Shurflo deliver up to 4.0 gpm and 45 psi. They are constructed with a corrosion resistant coated seamless motor shell and sealed switch to provide excellent protection against the harsh marine environment. They come standard with 1/2" MPT ports. See page 66 for other port fittings and page 158 for service parts.

Model Number	Max GPM	Volts	Max Amps	Inlet/Outlet	Dimensions (H x W x L)
SF 2901-6213	2.0	12 vdc	4	1/2" MPT and 3/4" Barb	4.6" x 5.0" x 7.6"
SF 3901-2214	3.5	12 vdc	9	1/2" MPT and 3/4" Barb	5" x 4.6" x 7.3"
SF 3901-3214	3.5	24 vdc	4.5	1/2" MPT and 3/4" Barb	5.4" x 5.3" x 7.2"
SF 4901-4282	4.0	12 vdc	10	1/2" MPT and 3/4" Barb	5" x 4.6" x 7.3"
SF 4901-5282	4.0	24 vdc	5.5	1/2" MPT and 3/4" Barb	5.4" x 5.3" x 7.2"



3.5 AND 5.2 GPM, 70 PSI JOHNSON WASHDOWN PUMPS

The new "Aqua Jet" 5 chambered diaphragm pumps by Johnson deliver up to 5.0 gpm and 70 psi. They will prime up to 6 feet and come complete with intake strainer, spray nozzle and 1/2" barbed fittings.

Model Number	Max GPM	Volts	Fuse Size	Inlet/Outlet	Dimensions (H x W x L)
JS 10-13399-03	3.5	12 vdc	15A	1/2" MPT and 3/4" Barb	4.57" x 8.25" x 9.31"
JS 10-13399-04	3.5	24 vdc	8A	1/2" MPT and 3/4" Barb	4.57" x 8.25" x 9.31"
JS 10-13407-07	5.2	12 vdc	20A	1/2" MPT and 3/4" Barb	4.33" x 8.43" x 9.46"
JS 10-13407-08	5.2	24 vdc	10A	1/2" MPT and 3/4" Barb	4.33" x 8.43" x 9.46"

