

# JABSCO DELUXE FLUSH TOILETS

- CONTENTS
- ENGINE COOLING
- INDEX
- HOME
- NEXT
- BACK



## JABSCO DELUXE ELECTRIC TOILETS

This stylish and extremely compact design is carefully contoured to conceal the flush pump, wiring and plumbing while still featuring a full-size household seat. All aspects of the design have been optimized for minimal water usage and near silent operation.

The two models differ only in the shape of the back of the toilet. The Slant Back version gives a minimal footprint and makes it easy to mount against a sloping surface or in a corner. The straight back version allows snug fitting against a vertical bulkhead.

Deluxe Flush toilets feature a multifunction 'one touch' pad offering 4 rinse and flush options, using as little as 1.5 US Quarts (1.5 liters) of water.

- Space saving elegant design
- Household size seat
- Virtually silent operation for comfort on board
- Choice of 4 'one touch' flush cycles for minimum water usage - 1.5 US Quarts (1.5 liters)
- Fresh or salt water flush options
- Anti-blocking centrifugal flush pump
- High gloss vitreous china bowl, for easy cleaning
- Complies with USCG 183.410 and ISO 8846 MARINE (Ignition Protection)

1. The Deluxe flush toilet series features a multi-function 'one touch' control pad offering four options- Fill, Quick Flush, Flush or Empty.
2. The 58020 and 58040 series are supplied with a solenoid valve and siphon breaker assembly for connection to any pressurized water system capable of delivering 3 gpm or more. The siphon breaker ensures that there is no back flow from the toilet into the water system.
3. The 58220 and 58240 series are supplied with a remote mounted self-priming pump to bring in sea, river or lake water to flush.



## DELUXE FLUSH SLANT BACK ELECTRIC TOILETS

Listed below are the slant back models, which are available in two water supplies (solenoid valve or intake pump) and two voltages (12 or 24 vdc). Service kits: 58100-1000 major kit, 58101-1000 ceramic seal kit.

Model Number	Color	Water Source	Volts	Fuse	Inlet/Outlet	Dimensions (H x W x L)
58020-1012	White	Solenoid Valve	12 vdc	25 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"
58020-1024	White	Solenoid Valve	24 vdc	15 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"
58220-1012	White	Intake Pump	12 vdc	25 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"
58220-1024	White	Intake Pump	24 vdc	15 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"



## DELUXE FLUSH STRAIGHT BACK ELECTRIC TOILETS

Listed below are the straight back models, which are available in two water supplies (solenoid valve or intake pump) and two voltages (12 or 24 vdc). Service kits: 58100-1000 major kit, 58101-1000 ceramic seal kit.

Model Number	Color	Water Source	Volts	Fuse	Inlet/Outlet	Dimensions (H x W x L)
58040-1012	White	Solenoid Valve	12 vdc	25 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"
58040-1024	White	Solenoid Valve	24 vdc	15 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"
58240-1012	White	Intake Pump	12 vdc	25 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"
58240-1024	White	Intake Pump	24 vdc	15 amps	3/4" Barb/ 1 1/2" Barb	17 1/4" x 14 1/2" x 17 1/2"