

# SUBMERSIBLES

## UP TO 88 GPM, 55 TDH STAINLESS STEEL SUMP & EFFLUENT

Cat stainless steel submersible pumps are available with or without an automatic switch, can pass solids to 3/8", withstand temperatures to 122-140° F, and are supplied with a 20 foot electric cord. Sizes range from 1/3 to 1 1/2 hp and come with a 1 1/4" or 1 1/2" discharge port.

MODEL	HP	CAPACITY IN GALLONS PER MINUTE (GPM)										
		FEET OF HEAD										
		5	10	15	20	25	30	35	40	45	50	55
1K100-103	1/3	45	39	31	21	5	-	-	-	-	-	-
1K201-205	1/2	-	73	67	60	51	40	27	9	-	-	-
1K301-305	3/4	-	-	-	74	67	58	49	39	28	16	-
1K404-405	1	-	-	-	-	82	75	65	55	42	27	-
1K504-505	1 1/2	-	-	-	-	88	81	74	65	54	43	25



## UP TO 185 GPM, 46 TDH STAINLESS STEEL SEWAGE PUMPS

Cat stainless steel submersible sewage pumps are available with or without an automatic switch, can pass solids to 2", withstand temperatures to 104-140° F, and are supplied with a 25 foot electric cord. Sizes range from 1/2 to 2 hp and come with a 2" discharge port.

MODEL	HP	CAPACITY IN GALLONS PER MINUTE (GPM)														
		FEET OF HEAD														
		8	9	10	12	14	16	18	21	24	27	30	32	35	40	46
2K100-105	1/2	88	83	78	68	57	45	31	8	-	-	-	-	-	-	-
2K200-205	1	-	-	-	100	88	76	64	45	25	8	-	-	-	-	-
2K302-305	1 1/2	-	-	120	113	105	97	84	69	52	30	8	-	-	-	-
2K403-405	2	-	180	177	171	165	158	152	141	130	118	105	96	81	52	8



## UP TO 110 GPM, 35 TDH CAST IRON SEWAGE PUMPS

Little Giant cast iron submersible sewage pumps are available with or without an automatic switch, can pass solids to 2", withstand temperatures to 120° F, and are supplied with a 15 or 20 foot electric cord. Sizes range from 4/10 to 1 hp and come with a 2" or 3" discharge port.

Series Number	HP	Port Size	GPM at Feet of Head			Max. Head
			5'	10'	20'	
LG 9S	4/10	2"	80	50	-	18'
LG 10S	1/2	2" or 3"	110	85	-	20'
LG 14S	1/2	2" or 3"	-	100	35	25'
LG 16S	1	3"	-	160	100	35'



## UP TO 480 GPM, 120 TDH SEWAGE SELF-PRIMER!

No, this is not a submersible pump. However, it's a great alternative! This rugged cast iron self-priming pump has a silicon carbide seal, stainless steel semi-open clog resistant impeller, built-in check valve and rear pullout design. It will lift up to 20 feet and is available in sizes from 3 to 15 hp and comes in 2", 3" and 4" ports. All sizes except the 4" are available in single or three phase. (See page 63 for complete flow curve.)

Model	HP	Port Size	GPM at Total Feet of Head					Max Head
			20'	40'	60'	80'	100'	
316A(B)-95	3	2"	100	60	-	-	-	60
393A(B)-95	5	2"	150	130	100	65	10	105
394A(B)-95	7.5	3"	275	225	160	80	-	95
394C(D)-95	10	3"	330	290	230	160	50	108
399A-95	15	4"	480	480	360	250	120	120

