

SHERWOOD



3/4", 1" & 1 1/4" Bronze Series

UP TO 37 GPM, 25 PSI, IN BRONZE

These versatile pumps mount on a standard 56C face, allowing a wide range of drive types and voltages to be accommodated. They are self-priming, pulse free, and have the ability to pass small particles in suspension, mild abrasives, and shear sensitive and/or viscous fluids. Each pump comes equipped with a stainless steel shaft, cover and wearplate, Nitrile (Buna) lip seal and cover o-ring, of either Neoprene or Nitrile impeller. An optional vacuum switch is available for dry run shutdown protection.

- Bronze housing, stainless shaft, cover and wearplates
- Nitrile lip seal, o-rings and impeller
- Versatile 56C face mounting
- Self-priming design
- Includes counterbalanced handle assembly

GALLONS PER MINUTE @ TOTAL PSI

SERIES	PORT SIZE	HP	RPM	FREE FLOW	5 PSI	10 PSI	15 PSI	20 PI	25 PSI
MRB9001	1/2"	1/3	1725	7.4	7.1	6.6	5.9	5.2	4.1
MRB9002	1/2"	1/2	3450	12.1	11.7	10.5	9.2	7.9	7.0
MRB9901	3/4"	1/2	1725	11.6	11.2	10.2	9.0	7.1	5.1
MRB9902	3/4"	3/4	3450	19.4	18.8	17.9	17.0	15.9	14.9
MRB15001	1"	3/4	1725	21.1	20.4	19.0	17.5	15.9	13.3
MRB15002	1"	1	3450	37.5	36.7	34.6	32.1	28.9	23.6

SHERWOOD



3/4", 1" and 1 1/4" Stainless Series

UP TO 37 GPM, 25 PSI, IN 316 STAINLESS

This series also mounts on a standard 56C face, allowing a wide range of drive types and voltages to be accommodated. They are self-priming, pulse free, and have the ability to pass small particles in suspension, mild abrasives, and shear sensitive and/or viscous fluids. This series features a viton mechanical shaft seal and cover o-ring, Teflon coated interior and either a Neoprene or Nitrile impeller. An optional vacuum switch is available for dry run shutdown protection.

- 316 stainless steel housing, shaft and cover
- Viton mechanical seal and Teflon coated wearplates
- Nitrile impeller
- Versatile 56C face mounting
- Self-priming design

GALLONS PER MINUTE @ TOTAL PSI

SERIES	PORT SIZE	HP	RPM	FREE FLOW	5 PSI	10 PSI	15 PSI	20 PSI	25 PSI
MRS9001	3/4"	3/4	1725	7.4	7.1	6.6	5.9	5.2	4.1
MRS9002	3/4"	1	3450	12.1	11.7	10.5	9.2	7.9	7.0
MRS9901	1"	1	1725	11.6	11.2	10.2	9.0	7.1	5.1
MRS9902	1"	1 1/2	3450	19.4	18.8	17.9	17.0	15.9	14.9
MRS15001	1 1/4"	1 1/2	1725	21.2	20.4	19.0	17.5	15.9	13.3
MRS15002	1 1/4"	2	3450	37.5	36.7	34.6	32.1	28.9	23.6

FOR ENGINEERING AND PUMP SELECTION ASSISTANCE CALL DEPCO AT 1-800-446-1656