

The Jabsco flexible impeller pumps are widely used throughout the food, dairy, beverage, and pharmaceutical industries. Inexpensive to buy and operate, their gentle pumping action effectively handles thin, viscous, shear sensitive, and particle-laden fluids.

- Up to 60 PSI
- Up to 185 GPM
- Sanitary clamp or acme threaded ports
- Gentle solid handling action
- Self-priming
- Close-coupled or pedestal mount
- 316 SS construction
- FDA compliant elastomers

**UNIQUE DESIGN and EASY MAINTENANCE**

**FLEXIBLE IMPELLER**  
Resilient, specially compounded elastomers; rugged and tear-resistant; non-toxic, tasteless and odorless.

**PORT CHOICES**  
Inlet and discharge ports are available with bevel seat sanitary threaded or sanitary clamp ports.

**O-RING GASKET**  
Made of neoprene. Other materials available.

**EASY CLEANING**  
Simply remove eight screws and disassemble by hand right down to the bearing housing. Design speeds cleaning operation – no special tools are needed.

**REPLACEABLE WEAR PLATE**  
316 Stainless steel, incorporating seal seat.

**SHAFT**  
316 Stainless Steel.

**BEARINGS THAT LAST**  
These heavy-duty ball bearings designed for belt drive or direct coupling are lubricated and sealed to eliminate the need for periodic servicing and maintenance and provide protection under severe washdown procedures.

**PUMP BODY**  
Polished 316 Stainless Steel. May be rotated in 90° increments to position ports for ease of piping connection.

**MECHANICAL SEAL**  
The seal is offered with carbon face or tungsten carbide for abrasive pumpage. Elastomers are of FDA listed materials.

VISCOSITY S.S.U	PUMP SPEED (Max. RPM)	VISCOSITY S.S.U.	PUMP SPEED (Max. RPM)	VISCOSITY S.S.U.	PUMP SPEED (Max. RPM)	VISCOSITY S.S.U	PUMP SPEED (Max.RPM)
50	1750	700	1680	4,000	1400	15,000*	787
100	1750	800	1645	5,000	1312	20,000*	700
200	1750	900	1610	6,000	1225	30,000*	612
300	1750	1,000	1574	7,000	1138	40,000*	525
400	1750	1,500	1540	8,000	1050	50,000*	437
500	1750	2,000	1505	9,000	962	75,000*	298
600	1715	3,000	1450	10,000	875	100,000*	175

\*Use High Pressure Impeller

**FOR ENGINEERING AND PUMP SELECTION ASSISTANCE CALL DEPCO AT 1-800-446-1656**