

SUBMERSIBLES

LITTLE GIANT



Submersible Series

UP TO 810 GPH, 24' TDH SMALL SUBMERSIBLE IN 115 VAC

These small submersibles are designed to run completely submerged in waterfalls, fountains, freshwater baitwells, machine tool coolant, lightweight oil transfer, mild chemical recirculation applications. These pumps are sealed and oil filled (except for NK series). The NK "No-Korode" series is designed to be used in mild acids, alkalis and hard water applications.

Model Number	Watts	GPH at Feet of Head				Max. Head	Outlet MPT	Dimensions in Inches (H x W x L)
		1'	3'	5'	10'			
LG P-AAA	30	120	70	-	-	4.6	1/4"	3 7/8 x 3 7/8 x 3
LG 1-MA	70	170	127	70	-	6.1	1/4"	4 1/4 x 3 9/16 x 3 3/8
LG 1	70	205	168	120	-	7.4	1/4"	4 1/4 x 4 1/8
LG 1-A	70	170	127	70	-	6.1	1/4"	4 1/4 x 4 1/8
LG 4E-34N	210	710	690	670	580	23.1	3/4"	5 1/2 x 7 x 4 1/2
LG 4E-34NR	210	810	790	745	613	24.5	1/2"	5 1/2 x 7 x 4 1/2
LG NK-1	70	210	180	150	-	10.0	1/4"	4 9/16 x 4 1/8 x 4 1/8
LG NK-2	100	325	300	270	130	12.3	1/4"	4 9/16 x 4 1/8 x 4 1/8

LITTLE GIANT



Mag-Drive Submersible Series

UP TO 1150 GPH, 16' TDH MINIATURE SUBMERSIBLE IN 115 VAC

These workhouse pumps, primarily used in fountain and water effect applications, were designed to operate continuously with minimum energy consumption. The screened inlets keep harmful debris from running through the pump. 115 vac pronged cords are standard. Sizes from 47 gph up to 1150 gph.

Model Number	AC Volts	Watts	GPH at 1 foot	Max. Head	Warranty
LG PES Series	115	110 Max	Up to 1150	Up to 16'	3 years

LITTLE GIANT



Submersible or In-line Series

UP TO 670 GPH, 20' TDH SMALL SUBMERSIBLE OR IN-LINE

These dual purpose pumps may be used either totally submerged, in open air, or in a closed loop installation. These pumps are hermetically sealed and filled with a special oil that provides lifetime lubrication and heat dissipation.

Model Number	GPH at Feet of Head				Max. Head	In/Outlet NPT	Dimensions in Inches (H x W x L)
	1'	3'	5'	10'			
LG 2E-38N	300	255	205	70	11.8	3/8"F / 1/4"M	5 1/2 x 4 3/4 x 3 1/2
LG 3E-12N	500	435	337	210	17.3	1/2"F / 1/2"M	7 x 5 1/2 x 4 1/2
LG 3E-34N	670	650	575	460	20.3	3/4"F / 1/2"M	7 x 5 1/2 x 4 1/2

LITTLE GIANT



5-MSP Series

UP TO 1200 GPH, 26' TDH UTILITY SUBMERSIBLE IN 115 VAC

These utility submersible pumps will pump down to 1/8" in depth under manual control. Automatic versions are also available with diaphragm or float switches. Each pump has a 1" FPT outlet with 3/4" garden hose adapter and a removable inlet screen for easy cleaning.

Model Number	GPH at Feet of Head			Max. Head	Switch On/Off	Switch Type	Cord Length
	1'	10'	20'				
LG 5MSP-25	1200	1000	650	26.3	Manual	None	10'
LG 5MSP-25	1200	1000	650	26.3	Manual	None	25'
LG 5ASP-FS	1200	1000	650	26.3	6" - 9" / 1" - 4"	Float	10'
LG 5ASP-LL	1200	1000	650	26.3	2" - 3" / 1/2" - 1 1/2"	Diaphragm	18'