

UP TO 43 GPM, 25' TDH, HEAVY-DUTY 12 VDC

The Gorman-Rupp 12 volt submersible pump is designed for use with a truck battery as a back-up unit in the event of power failure or for use in remote locations where electricity is not available. The pump weighs 28 pounds and is constructed of aluminum with a cast iron impeller. The 30 foot power cord has battery clips for easy attachment to a 12 volt battery. Operating time is approximately 45 minutes on a fully charged 55 amp-hour battery.

Gorman-Rupp Part Number	Warren-Rupp Part Number	Volts DC	Amps	GPM at Feet of Head				Weight in lbs
				5	10	20	25	
AM S1-1/2B3-E.33 12V	WR SPA-1 1/2E	12	30	43	40	30	21	33

GORMAN-RUPP



Dewatering

UP TO 6.5 GPM, 12.5' TDH "OIL FREE" EPOXY ENCAPSULATED

March epoxy encapsulated submersible pumps eliminate any possibility of oil contamination that is possible with the "oil filled" varieties. The models with a TE type motor (see below) may also be run in open air "non-submerged" applications. Maximum liquid temperature is 130°F and standard voltage is 115 vac (230 vac is available).

Model Number	GPM at Feet of Head				Max Head	Motor Type	Inlet Port	Outlet Port
	1'	3'	5'	10'				
MA 1C	1.9	.75			2.3'	TE/Sub	3/8" FPT	1/4" MPT
MA 1U	1.9	.75			2.3'	Sub	Screen	1/4" MPT
MA 1-1C	4.3	3.3	2.1		7'	TE/Sub	3/8" FPT	1/4" MPT
MA 1-1U	4.3	3.3	2.1		7'	Sub	Screen	1/4" MPT
MA 2C	6.4	5.8	5.0	2.6	12.5'	Sub	3/8" FPT	1/4" MPT
MA 2U	6.4	5.8	5.0	2.6	12.5'	Sub	Screen	1/4" MPT
MA LC-2C	6.4	5.8	5.0	2.6	12.5'	TE/Sub	3/8" FPT	1/4" MPT

MARCH



Epoxy Encapsulated Series

UP TO 300 GPH, 12' TDH PARTS WASHER SUBMERSIBLES

These Little Giant submersible pumps were specifically designed for cleaning solvent and soluble machine oil circulation. They are fitted with Viton seals, have oil filled motors, and nylon volutes and impellers. The motor housings are cast aluminum. 115 vac 1ph 60 hz standard.

Model	Maximum GPH	Max Head	Max Temp	UL Listed
LG 1-EAYS	170	7'	120°F	Yes
LG 2E-NYS	300	12'	120°F	Yes

LITTLE GIANT



Submersible Series

AUTOMATIC SUBMERSIBLES FOR SUMPLESS AREAS

Little Giant manufactures two very versatile submersibles for automatically removing water from areas without a sump (roof, patio, plant floor, etc.). Both pumps switch on at approximately 2 3/8" and shut off at 1 1/2" of water. Both models are 115 vac and come with a 25' electric cord.

Model Number	Volts	GPH at Feet of Head				Max Head	Outlet Port
		1	3	5	10		
LG 500-APCP	115 vac	470	356	252	-	9.2	3/4" GHT
LG 5-APCP	115 vac	1200	1170	1100	1000	26.3	1" FPT or 3/4" GHT

LITTLE GIANT



Automatic On/Off Series