


SELF-PRIMING CENTRIFUGALS

MP FLOMAX



1 1/2" or 2" Cast Iron, Brz. or Alum.




UP TO 160 GPM, 95' TDH

- Temperatures to 300° F
- Self-priming to 25'
- Will pass solids up to 9/16"
- Viton® mechanical seal standard, EPDM or Teflon® available, double seal options
- Construction: cast iron, bronze or aluminum wet ends
- **Flomax 8 available in 316SS**
- Drive Options: include electric close-coupled, pedestal mount, hydraulic, electric or manual clutch, and gas/diesel engine drive

MP FLOMAX



2" or 3" Cast Iron, Brz. or Alum.




UP TO 300 GPM, 130' TDH

- Temperatures to 300° F
- Self-priming to 25'
- Will pass solids up to 5/8"
- Viton® mechanical seal standard, EPDM or Teflon® available
- Construction: cast iron, bronze or aluminum wet ends
- **Flomax 15 available in 316SS**
- Drive Options: include electric close-coupled, pedestal mount, hydraulic, electric or manual clutch, and gas/diesel engine drive

MP FLOMAX 30




3" Cast Iron, Bronze or Aluminum




UP TO 480 GPM, 170' TDH

- Temperatures to 300° F
- Self-priming to 25'
- Will pass solids up to 5/8"
- Construction: cast iron or bronze
- Fully open impeller
- Drive Options: include electric close coupled, pedestal mount, and gas/diesel engine drive

MP HHLF



1 1/2" or 2" Cast Iron or Bronze



UP TO 150 GPM, 190' TDH

- Temperatures to 300° F
- Self-priming to 25'
- Will pass solids up to 1/4"
- Viton® mechanical seal standard
- Construction: cast iron or bronze
- 1 1/2" x 1 1/2" or 2" x 2" sizes
- Drive Options: Include electric close coupled, pedestal mount, hydraulic, electric or manual clutch and gas/diesel engine drive