

# BELLOWS AND PERISTALTIC METERING

## UP TO 100 GPD, 125 PSI

Pulsafeeder's Chemtec peristaltic metering pumps offer value, reliability and precision performance. Available fixed rate, adjustable rate, or with a programmable 7 day timer. Great for handling hard to pump chemicals like sodium hypochlorite or peroxide which tend to go to gas causing priming issues. Problem solved with ChemTech! Neoprene tubing, PVC fittings and polycarbonate head.

Model	Rate Range	Max Pressure	Control
XPV	.08 to 100 gpd	125 psi	115 or 230 vac 50/60 hz variable speed
XP	.2 to 80 gpd	125 psi	115 or 230 vac 50/60hz fixed rate or variable
CTP	.35 to 60 gpd	125 psi	115 or 230 vac 50/60hz fixed rate or variable

## CHEMTECH



XP and CTP Series

## UP TO 170 GPD, 100 PSI, AC AND DC

The Stenner line of peristaltic metering pumps offer dependable self-priming fluid metering or dispensing that will not lose its prime or clog from dirt or minor debris. In fact it will handle up to 50% slurry mixtures. One or two individually adjustable heads can be mounted on a single drive. Models vary in RPM, hose size and voltage. Motors are 1/30 hp and are available in 120 and 220 vac 50/60 hz, 230V 50 hz and 12 vdc.

Series Number	Number of Heads	Min GPD	Max GPD	RPM
45 Series	1	.2	50	26
85 Series	1	.3	85	44
100 Series	2	.3	100	26
170 Series	2	.5	170	44

## STENNER



170 gpd, 100 psi

## UP TO 3000 ML/MIN, 50 PSI BELLOWS PUMPS

GRI manufactures bellows metering pumps from compact configurations to stainless steel enclosed multi-headed versions. All models have adjustable strokes, various rpms, EPT, Hypalon® or Viton® elastomers and Polypropylene or Kel-F bellows. The standard and Bel-O-Just® series can handle up to 5,000 centistokes viscosity and fine slurries with standard poppet valves, heavy slurries and fibrous materials with upgraded duckbill valves. Temperatures to 140° F.

Bellows Module Output Per Full Stroke				
1/2"	3/4"	1"	1 1/2"	2"
.5 ml	1.8 ml	5 ml	10.5 ml	18 ml
Pump Series	RPM	Number of Bellows	Max. Flow/Minute	Max PSI
Mini-16200	8, 15 or 24	1	270 ml	6
Mini-16220	8 or 12	2	270 ml	6
Compact - 16000	38, 45.6, 75 or 90	1, 2, 3 or 4	1620 ml	5
Standard	39, 60, 90 or 165	1 to 3	3000 ml	50
Bel-O-Just	39, 60, 90 or 165	1 to 3	3000 ml	50

## GRI



OEM and LAB Bellows

## IWAKI OEM REPLACEMENT BELLOWS PUMPS

The Iwaki bellows metering pumps are available with a wide range of configurations from single to multiple head and custom mounts. Pumps are available in 30, 33, 50, 67 and 135 RPM and have 1", 1 1/2" or 2" diameter bellows. Elastomer options include EPDM and FKM. You will find Iwaki pumps on OEM equipment in the photographic, plating and electronic industries. Custom pumps designed to meet your requirements are available. All models are available in 110, 115 or 230 vac 50/60 hz. Temperatures to 140° F.

Pump Series	RPM	Max PSI	Max Flow	Number of Heads
SP Series	33, 67 or 135	10	2100 ml	1
DP Series	33, 67 or 135	10	2100 ml per Head	2
C Series	30 or 50	5	740 ml per Head	3 to 12
KBA Series	12, 15, 22, 24 or 36	5.7	360 ml per Head	1 to 3
KBR Series	12 or 24	1.4	216 ml	1

## IWAKI



Adjustable Bellows