

# GENERAL PURPOSE ENGINE COOLING

## JABSCO




51510-9001

### 3/8" PORT, UP TO 5 GPM, MECHANICAL SEAL DESIGN

Jabsco's 51510 incorporates the cam offset into the pump housing providing longer impeller and pump housing life. Designed to take the side load of being belt driven and utilize two ball bearings, mechanical seal and cover o-ring (instead of paper gasket). The 51510 interchanges with Johnson model #10-35038 (F35B-8 series).

Model Number	Port Size	Shaft Size	Impeller	GPM at RPM at 20 TDH				Dimensions (H x W x L)
				500	1000	2000	3000	
JA 51510-9001	3/8" FPT	12mm	22405-0001	.5	1.5	3.5	5.25	2 3/8" x 3" x 3 5/8"
JA 51510-2001	3/8" BSP	12mm	22405-0001	.5	1.5	3.5	5.25	2 3/8" x 3" x 3 5/8"

## JABSCO



51520-9001

### 1/2" PORTS, UP TO 8 GPM, MECHANICAL SEAL DESIGN

Similar to the 51510 Series pump above, Jabsco's 51520 Series 1/2" pump incorporated the cam offset into the longer impeller and housing life. It is a true general purpose pump and can be used for applications such as engine cooling, bilge and water circulation. Built for heavy duty use it is designed with two ball bearings, a mechanical seal and cover o-ring (instead of a paper gasket). The pump interchanges with Johnson model #10-24074.

Model Number	Port Size	Shaft Size	Impeller	GPM at RPM at 20 TDH				Dimensions (H x W x L)
				500	1000	2000	3000	
JA 51520-9001	1/2" FPT	12mm	18653-0001	.7	2.6	5.7	8.72	3 1/2" x 3" x 3 3/4"
JA 51520-2001	1/2" BSP	12mm	18653-0001	.7	2.6	5.7	8.72	3 1/2" x 3" x 3 3/4"

## OBERDORFER



M Series

### 3/8" - 1 1/4" PORTS, UP TO 55 GPM, DOUBLE BEARING DESIGN

Oberdorfer bronze pedestal pumps utilize mechanical seals and a unique spaced double ball bearing design that prolongs pump life by more efficiently distributing belt load. The N200M pump is designed specifically to be dimensionally interchangeable with Johnson's 10-35038 (F35B-8 series) and Jabsco's 51510 series.

Model Number	Port Size	Shaft Size	Impeller	GPM at RPM at 20 TDH				Dimensions (H x W x L)
				800	1750	3000	3450	
OB N200M	3/8" FPT	12 mm	OB 2379	1.2	2.9	5.4	-	2.48" x 3.15" x 3.70"
OB 201M	1/2" FPT	1/2"	OB 6593	1.8	4.8	8.4	9.6	2.88" x 3.75" x 5.16"
OB N301M	3/4" FPT	5/8"	OB 6620	4.2	10.5	17.8	19.5	3.19" x 4.13" x 5.81"
OB 401M-02	1" FPT	5/8"	OB 7441	11.0	24.0	34.5	-	3.31" x 4.75" x 6.75"
OB 501M-05	1 1/4" FPT	1"	OB 7054	26.0	55.0	-	-	4.56" x 6.0" x 8.53"

## SHERWOOD



R and G Series

### 1/2" - 1" PORTS, UP TO 32 GPM, 2 BEARING DESIGN

The Sherwood "R" series distributes the belt load between a single ball bearing near the drive end of the shaft and a carbon bushing in the cover. The Sherwood "G" series utilizes a double ball-bearing design and a convertible mounting base that allows vertical or horizontal mounting. The "G" series also offers in-line or vertical ports for 1" or 1 1/4" hose.

Model Number	Pump Series	Port Size	Shaft Size	Port Config.	Impeller Kit	GPM at RPM at 10 PSI			Dimensions (H x W x L)
						1000	2000	3000	
SH R30G	R	1/2" FPT	1/2"	Vertical	10077K	3.8	6.5	8.0	2.85" x 3.5" x 5.28"
SH R50G	R	3/4" FPT	5/8"	Vertical	9959K	6.8	12.0	19.5	3.75" x 4" x 5.28"
SH R-102	R	1" FPT	5/8"	Vertical	10615K	10.9	19.5	32.0	4.25" x 5.5" x 6.66"
SH G-1	G	1" Hose	5/8"	In-line	9959K	6.8	12.0	19.5	4 1/4" x 5 1/4" x 5 1/4"
SH G-2	G	1" Hose	5/8"	Vertical	9959K	6.8	12.0	19.5	4 3/8" x 5 1/4" x 5 1/4"
SH G-4	G	1 1/4" Hose	5/8"	Vertical	10615K	10.9	19.5	32.0	4 15/16" x 5 1/4" x 5 5/8"